

## لیست قیمت فروردین ماه محصولات تحت شبکه داهوا

@lhua
























مدل ردیف















مشخصات فنی

خط ویژه: 021-62999021  
www.mipcctv.comشرکت فرارگستر  
Faragostar  
قیمت (ریال)

تصویر



















1	PSD81602-A360	8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10		Call
2	PSD8802-A180	4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Four 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 25fps@4096x1800+50/60fps@1080P Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10		Call
3	PFW8800-A180	4x2MP Multi-Sensor Panoramic Network IR Bullet Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function  Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/2 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10, PoE+		Call
4	PFW8601-A180	3x2MP Multi-Sensor Panoramic Network IR Bullet Camera Three 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x832, 3.6mm fixed lens, Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function  Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10, PoE+		Call
5	PDBW8800-A180	4x2MP Multi-Sensor Panoramic Network IR Dome Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function  Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10, PoE+		Call
6	IPC-EBW8842-A5	8MP IR Fisheye WizMind Network Camera 8MP 1/1.7" CMOS image sensor, low luminance, and high definition image Min. Illumination 0.01 Lux@F2.0 (Color, 30 IRE), 0.001 Lux@F2.0 (B/W, 30 IRE), 0 Lux (Illuminator on) Focal Length 1.85mm, Field of View Horizontal: 185°; Vertical: 180° Outputs max. 8M (3280 × 2480) @25/30 fps Built-in IR LED, and the max. illumination distance is 10 m IVS: Intrusion, tripwire, heat map, people counting, Smart Search DWDR, HLC, BLC, AWB, AGC, 3D DNR, Roi, Defog, ICR, SMART H.264 +/H.265+ Built-in Dual Array Mic and Speaker, Audio in/out 1/1, Alarm in/out 2/2, Micro SD 256GB 12V DC/PoE, IP67 and IK10 protection		324.500.000
7	ITC237-PW1B-IRZ	دوربین ANPR با قابلیت تشخیص پلاک مناسب برای ورودی های پارکینگ 2 Megapixel Full HD WDR Access ANPR Camera -Embedded with LPR algorithm inside the camera -plate cutout, snapshot preview, recording -White list database, 1 ch relay out to control the barrier performance for outdoor applications- 1/2.8" 2Megapixel progressive scan CMOS H.265/H.264M/H.264H/H.264B dual-stream encoding 25/30fps@1080P(1920x1080), 2.7mm~12mm Motorize lens WDR(140dB), BLC, HLC, Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card 64GB, IR Distance 3~8m, IP67, IK10, PoE		181.500.000











8	IPCS831EP-ZE	 	1/2.5" 8 Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) 2.7mm ~12mm motorized lens, Max. Aperture F1.6 WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card memory , 128 GB, 1/1 Audio In/Out, 2/1 Alarm In/Out Max. IR LEDs Length 50m , Smart IR, IP67,IK10, PoE (Tripwire Intrusion Object Abandoned/Missing Face)		136.500.000
9	IPC-HFW2549T-AS-IL	  	<b>NEW</b> 8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.7" Progressive CMOS image sensor, 8MP(3840×2160)@20fps, (2688×1520)@25/30fps Min. Illumination 0.008 Lux@F1.6 (Color, 30 IRE) 0.0008 Lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on) Illumination Distance up to 60 m (195.85 ft) (IR) up to 50 m (164.04 ft) (Warm light) Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate Intelligent monitoring: Intrusion, tripwire, SMD Plus Rol, WDR 120db, HLC, BLC, AWB, AGC, 3D DNR, Smart illumination Alarm in/out 1/1, Audio in/out 1/1, Built-in Mic, Micro SD 256GB 12 VDC/PoE, IP67, IK10, Metal Case		98.000.000
10	IPC-HFW2831T-ZAS-S2		8MP Lite IR Vari-focal Bullet Network Camera 8MP, 1/2.7" Progressive CMOS low illuminance 0.008 Lux@F1.5 high image definition 8MP@15fps & 4MP@25/30fps 2.7-13.5mm Motorized Lens SMART H.264+/H.265+, (MJPEG in Sub Stream) IVS Intrusion, Tripwire Micro SD 256GB, 1ch Audio I/O, 1ch Alarm I/O WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T		109.000.000
11	HF2831T-ZS-S2		8MP Lite IR Vari-focal Starlight Bullet Network Camera 1/2.7" progressive scan CMOS image sensor, low illuminance, high image definition Smart H.265+/H.264 codec, MJPEG, high compression rate, ultra-low bit rate 8MP (3840 × 2160) @ 15 fps, 2688×1520 @ 25/30 fps WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Region of Interest, Voltage Detection 2.7 mm-13.5 mm Motorized fixed lens Max. IR LEDs Length 60m, Micro SD card memory , 256 GB IP67, PoE, Smart Detection (Tripwire Intrusion)		107.800.000
12	IPC-HFW2831TP-AS-S2		8MP Lite IR Fixed-focal Bullet Network Camera 8MP, 1/2.7" CMOS image sensor max. 8MP (3840 × 2160) @ 15 fps, and supports 2688×1520 (2688 × 1520) @ 25/30 fps Smart H.265+/ Smart H.264+, H.265; H.264; H.264B; MJPEG (only supported by the sub stream) Built-in IR LED, max IR distance: 80m, 3.6mm Fixed LenZ Min. Illumination 0.009 Lux@F2.0 ONVIF (Profile S/Profile G/Profile T); CGI; Milestone; Genetec WDR(120db), 3D NR, HLC, BLC, AGC, AWB, Rol, Smart IR Intrusion, tripwire Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card 12V DC/POE power support supply, IP67, IK10		80.500.000
13	IPC-HFW2831S-S2		8MP Lite IR Fixed-focal Bullet Network Camera 1/2.7" Progressive CMOS image sensor, low illuminance, high image definition Illumination 0.009 Lux@F2.0 SMART H.264+/H.265+, MJPEG, high compression rate, ultra-low bit rate 8MP (3840 × 2160) @ 15 fps, and supports 2688×1520 (2688 × 1520) @ 25/30 fps WDR (120 db), 3D DNR, HLC, BLC, AGC, AWB, Rol, Smart IR Intrusion, tripwire, SD Card 256GB, IP67, PoE		73.700.000
14	IPC-HFW1830SP-0360B-S6		8MP 8MP 1/2.7" CMOS Entry IR Fixed-focal Bullet Network Camera Outputs max. 8MP@15fps, supports 2688 × 1520 (2688 × 1520) @ 25/30 fps Illumination 0.004 Lux@F2.0 (B/W, 30 IRE) H.265+&H.264+ high compression rate, and ultra-low bit rate. WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Built-in MIC 3.6mm fixed lens, Built-in IR LED, and the max. illumination distance is 30 m. 12 V DC/PoE power supply, IP67		63.800.000
15	HF2531TP-ZS		1/2.7" 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 15fps@5M(2592×1944)&25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Mirco SD card 128GB, Max IR LEDs Length 60m , Smart IR IP67, PoE, Smart Detection (Tripwire Intrusion)		94.600.000
16	DH-IPC-HFW5449T1-ZE-LED	  	4MP 1/1.8" CMOS image sensor, Full-color Vari-focal Warm LED Bullet WizMind Network Camera Outputs max. 4MP (2688 × 1520) @ 30 fps, Focal Length 2.7 mm-12 mm Min. Illumination 0.0005 Lux@F1.0 , S/N Ratio > 56 dB Built-in warm illuminator, and the max. illumination distance : 70 m ROI, SMART H.264+/H.265+, flexible coding, WDR 140db , 3D NR, HLC, BLC IVS (Perimeter Protection) : Tripwire; intrusion; fast moving, loitering detection, people gathering; parking detection, Face Detection, People Counting, Intelligent Search Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card , built-in Mic and speaker 12V DC/PoE power supply, ePoE, IP67 protection, SMD 3.0		181.500.000

17	HFWS442EP-ZE-0832	 	<p>4MP Pro AI IR Vari-focal, WizMind 1/1.8" 4Megapixel progressive scan CMOS H.265,H.264,H.264B,H.264H, MJPEG triple-stream encoding Max 25/30fps@4Mp(2688x1520), 50/60fps@2Mp(1920 x 1080) WDR(140dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, EIS, Defog, Region of Interest, 8mm-32mm Motorized lens, Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB Audio in/Out 1/1, Alarm In/Out 2/1 Smart Detection Tripwire, intrusion (Recognition of vehicle and people), Object Abandoned / Missing, fast moving, loitering detection, parking detection and people gathering Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas independent detection, Scene Change, Heatmap, IP67, IK10, PoE</p>		154.000.000
18	IPC-HFW5241E-Z5E	  	<p>2MP IR Vari-focal Bullet WizMind Network Camera 2MP 1/2.8" Progressive STARVIS™ CMOS low illuminance 0.0015 Lux@F1.3 high image definition 2MP@25/30fps 7-35mm Motorized Lens SMART H.264+/H.265+ IVS: Tripwire; intrusion; fast moving (with accurate classification of vehicle and human); loitering detection; people gathering; parking detection Face Detection with Face Attributes and Face Expression People Counting with Queue Management Micro SD card 256 GB, 1ch Audio I/O, 2/1 Alarm I/O WDR (120db), EIS, Defog, 3D DNR, HLC, BLC, AWB, AGC, Roi, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, 4 IR LEDs 120m Distance, Onvif Profile S/G/T</p>		134.200.000
19	IPC-HFW5541E-ZE-S3	  	<p>5MP IR Vari-focal Bullet WizMind Network Camera 5-MP (2960 x 1668) 1/2.7" CMOS image sensor, low luminance, and high definition image Super Low Illumination 0.0009 lux@F1.5(Color, 30 IRE) 0.0005 lux@F1.5(B/W, 30 IRE) 0 lux (Illuminator on 60m) 2.7 mm~13.5 mm Motorized Lens, Field of View H: 114°~32°; V: 58°~17°; D: 138°~36° Smart H.265+; Smart H.264+, AI Coding Deep learning algorithm, video metadata, smart sound detection, people counting, queue management, Heat Map, Smart Search face detection with 6 Face Attributes and 8 Face Expressions smart object detection: Smart abandoned object, smart missing object IVS: Intrusion, tripwire, fast moving, loitering, people gathering, parking detection SMD 3.0 ( Less false alarm, longer detection distance ) with detailed information about human body and vehicle features BLC, HLC, WDR 120db, Ai SSA, AWB, AGC, 3D DNR, Roi, EIS, Defog Built-in Mic, Audio I/O 1/1, Alarm I/O 2/1, Micro SD up to 512GB, ROM 4GB, RAM 1GB IP67 and IK10 protection</p>		170.500.000
20	DH-IPC-HFW4431TP-S-54		<p>4MP WDR IR Mini Bullet Network Camera 1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688x1520) H.265&amp;H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p>		60.750.000
21	DH-IPC-HFW3849T1-AS-PV-S3	 	<p>8MP Smart Dual Illumination Active Deterrence Fixed-focal Bullet WizSense Network Camera 1/2.8" CMOS image sensor, low illuminance, high image definition Outputs max. 8 MP (3840 x 2160)@25/30 fps Min. illumination 0.004 lux@F1.0 (Color, 30 IRE), 0.0004 lux@F1.0 (B/W, 30 IRE), 0 lux (illuminator on) Built-in warm illuminator, and the max. illumination distance: 30 m Intrusion, tripwire (support the classification and accurate detection of vehicle and human) WDR 120db, 3D NR, HLC, BLC, digital watermarking, Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256G SD card; <b>Dual Built-in Mic</b>; 1-ch speaker 12 VDC/PoE power supply, IP67 protection, Sound and light alarm (red and blue lights) SMD 3.0, One-click arming/disarming through alarm input</p>		129.800.000
22	IPC-HFW3849T1-AS-PV-S4	 	<p>8MP Smart Dual Light Active Deterrence Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.8" CMOS image sensor, low luminance, and high definition image Outputs max. 8 MP (3840 x 2160)@25/30 fps, H.265 codec, high compression rate, ultra-low bit rate Min. illumination 0.004 lux@F1.0 (Color, 30 IRE), 0.0004 lux@F1.0 (B/W, 30 IRE), 0 lux (illuminator on) Built-in warm light and IR LED; the max. IR illumination distance is 30 m and warm light distance is 30 m IVS: Intrusion, Tripwire, SMD 4.0, Quick Pick, Ai SSA, Ai Coding, WDR 120db, SSA, HLC, BLC, 3D DNR, Defog, AWB, AGC, Roi, ICR, Smart Illumination <b>Dual Built-in Mic</b>, Built-in Speaker, Audio in/out 1/1, Alarm Input 1 channel in: 5mA 3V~5 VDC, Alarm Output 1 channel out: 300mA 12 VDC, Micro SD 256G, support two-way talk Power Supply 12V DC/PoE (802.3af), IP67 protection, One-tap arming/disarming through alarm input, Sound and light alarm (red and blue lights)</p>		131.000.000
23	DH-IPC-HFW3449EP-AS-LED-3.6		<p>4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688x1520) H.265/Smart H.265+/H.264/Smart H264+ triple-stream encoding IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p>		73.000.000
























24	DH-IPC-HFW3449EP-AS-LED-2.8	<p>4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688×1520) H.265/Smart H.265+/H.264/Smart H264+ triple-stream encoding IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p>		73.000.000
25	HFHW3441TP-ZS-27135	<p>4MP IR Vari-focal Bullet WizSense Network Camera 1/3"4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.5 2.7 mm-13.5 mm Motorized lens 25/30fps@4Mp(2688×1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of vehicle and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p>		102.300.000
26	IPC-HFW2849S-S-IL	<p>8MP Smart Dual Light 2.8mm Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps Min. Illumination 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m WDR 120db, BLC, HLC, AWB, AGC, ROI, 3D DNR, ICR, Smart Illumination IVS: Intrusion, Tripwire, SMD Plus, Smart Search Built-in Mic, Micro SD 256GB 12 VDC/PoE (802.3af), IP67 Protection,</p>		77.000.000
27	IPC-HFW2841T-ZS	<p>8MP IR Vari-focal Bullet WizSense Network Camera 8-MP 1/2.7" Progressive CMOS image sensor 8MP(3840 × 2160)@20fps, (2688 × 1520)@25/30fps Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate Min. Illumination 0.008 lux@F1.5 (Color, 30 IRE) 0.0008 lux@F1.5 (B/W, 30 IRE) 0 lux (Illuminator on) Built-in IR LED, and the max. illumination distance is 60 m WDR 120db, BLC, HLC, AWB, AGC, ROI, 3D DNR, ICR, Smart Illumination Intelligent monitoring: Intrusion, tripwire, SMD Plus Built-in Mic, Micro SD 256GB, 12 VDC/PoE, IP67, IK10</p>		123.200.000
28	IPC-HFW2549T-AS-IL	<p>5MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera 5-MP 1/2.7" Progressive CMOS image sensor SMP(2960 × 1668)@20fps, (2688 × 1520)@25/30 fps Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate Focal Length 2.7 mm-13.5 mm Min. Illumination 0.007 lux@F1.6 (Color, 30 IRE) 0.0007 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on) Built-in warm light and IR LED, the max. IR light distance is 60 m and max. warm light is 50 m WDR, ROI, HLC, BLC, AWB, AGC, 3D DNR, Smart illumination Intelligent monitoring: Intrusion, tripwire, SMD Plus Alarm in/out 1/1, Audio in/out 1/1, Built-in Mic, Micro SD 256GB 12 VDC/PoE, IP67, IK10, Metal Case</p>		85.800.000
29	IPC-HFW2449S-S-LED	<p>4MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Min. Illumination :0.005 lux@F1.0 Built-in warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC 12 VDC/PoE power supply, easy for installation, IP67 protection, SMD Plus.</p>		54.500.000
30	DH-IPC-HFW2449S-S-IL	<p>4MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Min. Illumination : 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) Built-in warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC 12 VDC/PoE power supply, easy for installation, IP67 protection, SMD Plus.</p>		54.500.000
31	IPC-HFW2441S-S	<p>4MP IR Fixed-focal Bullet WizSense Network Camera 4-MP 1/2.9" Progressive CMOS image sensor, Outputs 4MP (2688 × 1520)@20 fps, and supports 2560 × 1440@25/30 fps Min. Illumination 0.006 Lux@F1.6(Color,30IRE) 0.0006 Lux@F1.6(B/W,30IRE) 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance is 30m ROI, SMART H.264 +/H.265+, WDR 120db, 3D NR, HLC, BLC, AWB, AGC, 3D DNR Intelligent monitoring: Intrusion, tripwire, SMD Micro SD card 256GB, built-in MIC, 12 VDC/PoE, IP67, Metal Case</p>		47.300.000










32	DH-IPC-HFW2441T-ZS		<p>4MP IR Vari-focal Bullet WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 ,(2560 × 1440)@25/30 fps Min. illumination, 0.008 lux@F1.5 (Color, 30 IRE), 0.0008 lux@F1.5 (B/W, 30 IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate, Focal Length 2.7 mm~13.5 mm Built-in IR LED, and the max. illumination distance is 60 m ROI, SMART H.264+/H.265+, flexible coding, WDR 120db, 3D NR, HLC, BLC Intrusion, tripwire (support the classification and accurate detection of vehicle and human) 256G SD card, <b>built in MIC</b> 12 VDC/PoE power supply, easy for installation, IP67, IK10 (optional) protection, SMD Plus</p>		92.400.000
33	IPC-HFW2439SP-SA-LED-0360B-S2		<p>4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>		50.850.000
34	HFW2431TP-AS-S2		<p>4MP Lite IR Fixed-focal Bullet Network Camera, 1/3" CMOS image sensor Outputs max. 4MP (2688 × 1520) @20 fps, and supports 2560×1440 (2560 × 1440) @25/30 fps Built-in IR LED, max IR distance: 80 m, Intelligent detection: Intrusion, tripwire H.265; H.264; H.264B; MJPEG(only supported WDR(120 dB), 3D NR, HLC, BLC, digital watermarking Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card 12V DC/POE, IP67 protection, IK10 protection (optional)</p>		62.150.000
35	HFW2431TP-ZS-S2		<p>4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps, 2560 × 1440 @25fps Min. illumination: 0.008 Lux@F1.5, 2.7~13.5 mm Motorized lens WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance: 60 m, Smart IR, IP67, PoE</p>		81.000.000
36	IPC-HFW1431S1-S4-S5		<p>4MP Entry IR Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.03 Lux @ F2.0 high image definition 4MP@25/30fps 3.6mm fixed lens, Smart H.265+/H.264+ WDR(120db), ROI, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, 1 IR LEDs 30m Distance, ONVIF (Profile S/Profile G/Profile T)</p>		34.650.000
37	HFW1431SP-0360B-S4		<p>4MP Entry IR Fixed-focal Bullet Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps, 2560 × 1440 @25fps Min. illumination: 0.03 Lux@F2.0, 3.6 Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance: 30 m, Smart IR, IP67, PoE</p>		40.700.000
38	HFW3541EP-AS		<p>5MP IR Fixed focal Bullet WizSense Network Camera 1/2.7" CMOS image sensor, Outputs max. 5MP (2592 × 1944) @20 fps H.265 codec SMART H.264+/H.265+ WDR(120db), 3D DNR, HLC, BLC, digital watermarking, Min illumination 0.0005 Lux@F1.6 (B/W, 30IRE) 12V DC/POE IP67 SMD Plus Supports max. 256 G Micro SD card, built-in Mic</p>		Call
39	IPC-HFW3549T1P-AS-PV		<p>5-MP 1/2.7" CMOS image sensor, low luminance, Smart Dual Illumination Min. illumination : 0.003 lux@F1.0 (Color, 30 IRE) / 0.0003 lux@F1.0 (B/W, 30 IRE) / 0 lux (illuminator on) Lens Fixed-focal 3.6 mm , 15.6 m Recognize &amp; 7.8 m Identify, Illumination Distance : 30 m (2 IR LED) / 30 m (2 warm light) AI H.265, AI H.264 , Smart H.265+, Smart H.264+, <b>Built-in MIC</b> Main stream: 2880 × 1620 or 2960 × 1668 @20fps / 2688 × 1520 @ (30 fps) WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI(4 years), Smart Illumination, Defog, Scene Self-adaption Storage : FTP, SFTP, Micro SD card (support max. 256 G), NAS ROM : 128MB, RAM : 512MB, S/N Ratio &gt; 56db , Sound and Light Alarm, Active Deterrence, IVS (Tripwire, intrusion), SMD 4.0, Smart Search, Quick Pick, AI SSA Audio In/out : 1/1 , Alarm in/out : 1/1, RJ-45 (10/100 Base-T) , 3.3 W (12 VDC); 4.4 W (PoE), IP67</p>		109.500.000
40	HFW3549EP-AS-LED-0360B		<p>5MP Full-color Fixed-focal Warm LED Bullet WizSense Network Camera 5MP, 1/2.7" CMOS image sensor low illuminance 0.003 Lux@F1.0 5MP@20 fps, 4MP@25/30 fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, Built-in warm light, max. illumination distance: 30 m, Onvif Profile S/G/T</p>		81.000.000

















مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
41	<p>IPC-HFW3541TP-ZS-27135</p> <p><b>STARLIGHT Wiz Sense</b></p> <p>5MP IR Vari-focal Bullet WizSense Network Camera 5MP, 1/2.7" Progressive CMOS 0.005 Lux@F1.5 (Color, 30IRE), 0.0005 Lux@F1.5 (B/W, 30IRE), 0 Lux (Illuminator on) high image definition 5MP@20fps 2.7-13.5mm Motorized Lens SMART H.264+/H.265+ 3 Streams IVS Intrusion, Tripwire, Accurate Human/Vehicle Classification, SMD Plus Micro SD 256GB WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T</p>		122.500.000
42	<p>IPC-HFW2531TP-AS-S2</p> <p><b>STARLIGHT</b></p> <p>5MP Lite IR Fixed-focal Bullet Network Camera 5MP, 1/2.7" Progressive CMOS low illuminance 0.008 Lux@F1.6 high image definition 5MP@20fps, 3.6mm fixed Lens SMART H.264+/H.265+, IVS Intrusion/Tripwire 1ch Alarm I/O, 1ch Audio I/O, Micro SD 256GB WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, IR LED 80m Distance, Onvif Profile S/G/T</p>		71.500.000
43	<p>HFW2431SP-S-S2</p> <p><b>STARLIGHT</b></p> <p>4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 x 1520)@20 fps, 2560 x 1440 @25fps Min. Illumination:0.008 Lux@F1.6, 3.6mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance: 30 m, Smart IR, IP67, PoE</p>		46.750.000
44	<p>HFW2249SP-S-IL-0360B</p> <p><b>Full-Color STARLIGHT Wiz Sense</b></p> <p>2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE) Outputs max. 2 MP (1920 x 1080)@25/30 fps, Fixed Lens 3.6mm Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B Built-in warm light/IR LED : 30m/30m ROI, WDR, 3D NR, HLC, BLC, digital watermarking SMD Plus, Intrusion, tripwire (two functions supported : detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC. 12 VDC/PoE power supply, easy for installation, IP67</p>		45.100.000
45	<p>HFW2249SP-S-IL-0280B</p> <p><b>Full-Color STARLIGHT Wiz Sense</b></p> <p>2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE) Outputs max. 2 MP (1920 x 1080)@25/30 fps, Fixed Lens 2.8mm Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B Built-in warm light/IR LED : 30m/30m ROI, WDR, 3D NR, HLC, BLC, digital watermarking SMD Plus, Intrusion, tripwire (two functions supported : detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC. 12 VDC/PoE power supply, easy for installation, IP67</p>		45.100.000
46	<p>HFW2231SP-S-0360B-S2</p> <p><b>STARLIGHT</b></p> <p>2MP WDR IR Bullet Network Camera, starlight 1/2.8" 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 x 1080) @25/30 fps, 3.6mm Fixed lens SMART H.264/H.265 dual-stream encoding, IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Rol Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p>		34.100.000
47	<p>HFW2230SP-S</p> <p><b>STARLIGHT</b></p> <p>2MP IR Bullet Network Camera 1/2.7" CMOS image sensor, low illuminance, high image definition H.265+/H.265/H.264+/H.264 Double-stream encoding 25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI 3.6mm, Max. IR LEDs Length 30m, Smart IR Micro SD card memory 128 GB, IP67, PoE, AVI(Tripwire Intrusion)</p>		33.000.000
48	<p>IPC-HFW2239SP-SA-LED-S2</p> <p><b>Full-Color</b></p> <p>2MP Lite Full-color Fixed-focal Bullet Network Camera 1/2.8" CMOS image sensor, Outputs max. 2MP (1920 x 1080) @25/30 fps ROI, SMART H.264+/H.265+, flexible coding, Min Illumination 0.0017 Lux@F1.0 Intelligent detection: Intrusion, tripwire WDR(120db), 3D NR, HLC, BLC, digital watermarking Supports max. 256 GB Micro SD card and built-in Mic, 12V DC/PoE, IP67</p>		41.250.000
49	<p>IPC-HFW2231T-ZS-S2</p> <p><b>STARLIGHT</b></p> <p>2MP Lite IR Vari-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS, low illuminance 0.002 Lux@F1.5 high image definition 2MP@25/30fps, 2.7-13.5mm Motorized Lens, SMART H.264+/H.265+ IVS Intrusion, Tripwire, Micro SD card 256 GB WDR(120db), Rol, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, IK10, 4 IR LEDs 60m Distance, Onvif Profile S/G/T</p>		71.500.000
50	<p>HFW1530SP-0360B-S6</p> <p><b>STARLIGHT</b></p> <p>5MP 1/2.7" CMOS image sensor Outputs max. 5MP (2880 x 1620) @20 fps, Fixed-focal 3.6mm min illumination 0.003 Lux@F2.0 (B/W, 30 IRE) H.265 codec, SMART H.264 +/H.265+ Built-in IR LED, and the max. illumination distance is 30 m Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking Built-in MIC, IP67, POE</p>		43.800.000










مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
51	<p><b>NEW</b></p> <p>4MP Entry Full-color Fixed-focal Bullet Network Camera 4-MP 1/3" Progressive CMOS image sensor, Outputs max. 4 MP (2560 × 1440)@25/30 fps Min. Illumination 0.008 lux@F1.6, Illumination Distance 15 m (49.21 ft) (warm light) SMART H.264+/H.265+, Rol, WDR 120db, BLC, HLC, AWB, AGC, 3D DNR, Smart Illumination Built-in Mic, 12 VDC/PoE, Metal + plastic, IP67</p>		40.500.000
52	<p>2MP Lite Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens SMART H.264+/H.265+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 15m Distance, Onvif Profile S/T</p>		30.250.000
53	<p>2MP Entry, 1/2.8" CMOS image sensor, low luminance, and high definition image Outputs max. 2MP (1920 × 1080)@25/30 fps. Min. Illumination : 0.008 Lux@F1.7 (Color, 30 IRE), 0.0008 Lux@F1.7 (B/W, 30 IRE) Motorized vari-focal, 2.8 mm-12 mm, IR Distance 50 m(2 IR) Smart H.265+, Smart H.264+, H.265 codec, high compression rate, ultra-low bit rate. DWDR, 3D DNR, HLC, BLC, AWB, AGC, Rol(4 years), Smart Illumination, S/N Ratio &gt; 56 dB 1 Port RJ-45 (10/100 Base-T), 12V DC/PoE (802.3af), IP67, Humidity ≤95%</p>		57.200.000
54	<p>2MP Entry IR Fixed-Focal Bullet Network Camera 1/2.8" CMOS image sensor, low illuminance Fixed Lens 3.6mm, F2.0, Horizontal: 84° Outputs max. 2MP (1920 × 1080) @25/30 fps Smart H.265+, Smart H.264+, H.265, H.264, H.264B ONVIF (Profile S/Profile T) Built-in efficient IR illuminator, and the max. illumination distance is 30 m ROI, DWDR, 3D NR, HLC, BLC, digital watermarking 2V DC/PoE power supply, IP67</p>		28.100.000
55	<p>2MP Entry IR Fixed-focal Bullet Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 3.6 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30m, Smart IR IP67, PoE</p>		29.700.000
56	<p>5MP IR Vari-focal Vandal-proof Dome WizMind Network Camera 5-MP (2960 × 1668) 1/2.7" CMOS image sensor, low luminance, and high definition image Super Low Illumination 0.0009 lux@F1.5(Color, 30 IRE) 0.0005 lux@F1.5(B/W, 30 IRE) 0 lux (Illuminator on 40m) 2.7 mm-13.5 mm Motorized Lens, Field of View H: 114°-32°; V: 58°-17°; D: 138°-36° Smart H.265+; Smart H.264+, AI Coding Deep learning algorithm, video metadata, smart sound detection, people counting, queue management, Heat Map, Smart Search face detection with 6 Face Attributes and 8 Face Expressions smart object detection: Smart abandoned object; smart missing object IVS: Intrusion, tripwire, fast moving, loitering, people gathering, parking detection SMD 3.0 ( Less false alarm, longer detection distance ) with detailed information about human body and vehicle features BLC, HLC, WDR 120db, Ai SSA, AWB, AGC, 3D DNR, Rol, EIS, Defog Built-in Mic, Audio I/O 1/1, Alarm I/O 2/1, Micro SD up to 512GB, ROM 4GB, RAM 1GB IP67 and IK10 protection</p>		170.500.000
57	<p>4MP IR Eyeball Network Camera 1/3" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688×1520) H.265&amp;H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Built-in Mic Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE</p>		52.800.000
58	<p>5MP IR Fixed-focal Dome WizSense Network Camera 5-MP (2960 × 1668) @20fps 1/2.7" CMOS image sensor, excellent low luminance performance and high definition of images 0.005 lux@F1.4 (Color, 30 IRE), 0.0005 lux@F1.4 (B/W, 30 IRE), 0 lux (Illuminator on 50m) 2.8 mm: Horizontal: 111°; Vertical: 58°; Diagonal: 132° Smart H.265+, Smart H.264+, AI Coding IVS: Tripwire, Intrusion, SMD 4.0, Smart Search, Scene Changing, Audio Detection BLC, HLC, WDR 120db, Ai SSA, AWB, AGC, 3D DNR, Rol, Defog, AFSA Built-in Mic, Micro SD up to 256GB, ROM 128MB, RAM 512MB IP67, IK10 protection, Easy Installation</p>		77.000.000









59	HDBW3441EP-AS	 	<p>4MP IR Fixed focal Dome WizSense Network Camera            1/3" CMOS image sensor Outputs max. 4MP (2688 × 1520)@30 fps            H.265 codec, SMART H.264+/H.265+            WDR(120db), 3D DNR, HLC, BLC, digital watermarking            Supports max. 256 G Micro SD card, 12V DC/PoE, IP67, IK10, SMD Plus            Min Illumination 0.0005 Lux@F1.6 (B/W, 30IRE)            Audio Input 1 channel (RCA port), Audio Output 1 channel (RCA port)            Alarm Input 1 channel in, Alarm Output 1 channel out</p>		62.700.000
60	HDW3441TMP-AS-0280B	 	<p>4MP IR Fixed focal Eyeball WizSense Network Camera            1/3" 4Megapixel progressive CMOS            Min. Illumination: 0.005 Lux@F1.6            2.8mm Motorized lens            25/30fps@4Mp(2688×1520)            SMART H.264+/H.265+ triple-stream encoding            IVS(Tripwire; intrusion (Recognition of human and vehicle))            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI            Built-in Mic, Micro SD memory 256GB            Max. IR LEDs Length 50m, Smart IR, IP67, PoE</p>		59.500.000
61	HDBW2831EP-S-S2	 	<p>1/2.7" 8Megapixel progressive CMOS            Min. Illumination: 0.009 Lux@F2.0            3.6mm Fixed Lens            max. 8MP (3840 × 2160) @15 fps, 2688×1520 (2688 × 1520) @25/30 fps            SMART H.264+/H.265+, flexible coding            IVS(Tripwire; intrusion), Abnormality detection: Motion detection, video tampering            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI            Micro SD memory 256GB            Built-in IR LED Max.Length 30m, IP67, PoE</p>		76.500.000
62	HDBW2531RP-ZAS		<p>1/2.7" 5Megapixel progressive CMOS            2.7~13.5mm Motorized lens            20fps@5M(2592×1944)&amp;25/30fps@3M(2304×1296)            H.265+/H.265/H.264+/H.264 dual-stream encoding            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC            1/1 Audio in/out, 1/1 Alarm in/out            Micro SD card 128GB            Max IR LEDs Length 30m ,Smart IR            IP67, IK10, PoE</p>		94.600.000
63	IPC-HDBW2531E-S-S2		<p>SMP Lite IR Fixed-focal Dome Network Camera            SMP, 1/2.7" Progressive CMOS            Min. Illumination 0.008 Lux @ F1.6            Max 5MP@20fps            SMART H.264+/H.265+            IVS: Intrusion, tripwire            Micro SD card 256GB            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI            max IR distance: 30m, 12V DC, PoE, IP67, IK10</p>		47.600.000
64	IPC-HDW2831TP-AS-S2		<p>8MP Lite IR Fixed-focal Eyeball Network Camera            1/2.7" CMOS image sensor Outputs max. 8MP (3840 × 2160) @15 fps            Min Illumination 0.009 Lux@F2.0            Built-in IR LED, max IR distance: 30 m            SMART H.264+/H.265+ WDR, 3D NR, HLC, BLC, digital watermarking            Supports max. 256 GB Micro SD card, <b>built-in MIC</b>            12V DC/PoE, IP67</p>		77.000.000
65	IPC-HDW2449T-S-LED	  	<p>4MP Full-color Fixed-focal Eyeball Wizsense Network Camera            4-MP 1/2.9" Progressive CMOS image sensor, 4MP(2688× 1520)@20fps, (2560×1440)@25/30fps            Min. Illumination 0.005 lux@F1.0, Built-in warm light, max. illumination distance 30m            Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate            ROI, WDR 120db, HLC, BLC, AGC, AWB, 3D DNR, Smart illumination            Intelligent monitoring: Intrusion, tripwire, SMD Plus            Built-in Mic, Micro SD 256GB            12 VDC/PoE, IP67, Metal+Plastic Case</p>		54.500.000
66	DH-IPC-HDW2449T-S-IL	  	<p>4MP Smart Dual Illumination 2.8mm Fixed-focal Eyeball WizSense Network Camera            Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps            Min. Illumination : 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on)            H.265 codec, high compression rate, ultra-low bit rate            Built-in warm light/IR LED, the max. illumination distance is 30 m            ROI, SMART H.264+/H.265+, flexible coding, WDR, 3D NR, HLC, BLC, digital watermarking            Intrusion, tripwire (support the classification and accurate detection of vehicle and human Supports max. 256 G Micro            SD card, built in MIC, 12 VDC/PoE power supply, easy for installation, IP67 protection, SMD Plus</p>		56.100.000












مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
67	<p>IPC-HDW2439TP-AS-LED-0360B</p> <p><b>STARLIGHT Full-Color</b></p> <p>4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 3.6mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, <b>Built-in Mic</b> 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>		52.000.000
68	<p>IPC-HDW2439TP-AS-LED-0280B-S2</p> <p><b>STARLIGHT Full-Color</b></p> <p>4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 2.8mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, <b>Built-in Mic</b> 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>		52.000.000
69	<p>DH-IPC-HDBW2441E-S</p> <p><b>STARLIGHT WizSense</b></p> <p>4MP 1/2.9" CMOS image sensor, IR Fixed-focal 2.8mm Dome WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2566 × 1440@25/30 fps Min. Illumination 0.008 lux@F1.6 (Color, 30IRE), 0.0008 lux@F1.6 (B/W, 30IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, WDR 120db, 3D NR, HLC, BLC Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card; <b>built in MIC</b> 12 VDC/PoE power supply, easy for installation, IP67, IK10 protection, SMD Plus</p>		51.500.000
70	<p>DH-IPC-HDBW2441R-ZS</p> <p><b>STARLIGHT WizSense</b></p> <p>4MP IR Vari-focal Dome WizSense Network Camera, 4-MP 1/2.9" CMOS image sensor Outputs max. 4 MP (2688 × 1520)@20 fps and supports 2560 × 1440 , (2560 × 1440)@25/30 fps Min. Illumination 0.008 lux@F1.5 (Color, 30 IRE) , 0.0008 lux@F1.5 (B/W, 30 IRE) , 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance : 40 m, ROI, SMART H.264+/H.265+ WDR 120dB, 3D NR, HLC, BLC, Focal Length 2.7 mm-13.5 mm Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); 256G SD card; <b>built in MIC</b> 12 VDC/PoE power supply, easy for installation, IP67 and IK10 protection, SMD Plus</p>		90.200.000
71	<p>IPC-HDW2441T-S</p> <p><b>STARLIGHT WizSense</b></p> <p><b>NEW</b></p> <p>4MP IR Fixed-focal Eyeball WizSense Network Camera 4-MP 1/2.9" Progressive CMOS image sensor, Output 4MP (2688 × 1520)@20 fps, 2560 × 1440@25/30 fps Min. Illumination 0.006 lux@F1.6 (Color, 30IRE) 0.0006 lux@F1.6 (B/W, 30IRE) 0 lux (Illuminator on) Smart H.265+; Smart H.264+, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance is 30 m WDR 120db, 3D NR, HLC, BLC, ROI, AWB, AGC, 3D DNR Intelligent monitoring: Intrusion, tripwire, SMD Plus Built-in Mic, Micro SD 256GB, IP67, 12 VDC/PoE, Metal+Plastic</p>		48.500.000
72	<p>HDBW2431RP-ZS-27135-S2</p> <p><b>STARLIGHT</b></p> <p>4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps, 2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7-13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE</p>		79.500.000
73	<p>HDBW2431RP-ZAS-S2</p> <p><b>STARLIGHT</b></p> <p>4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps, 2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7-13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE</p>		80.300.000










ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
74	HDBW2431EP-S-0360B-S2	<p>4MP IR Mini Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux @ F1.6 3.6 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB max IR distance:30 m, Smart IR IP67, IK10, PoE</p>		45.100.000
				
75	HDBW2431EP-S-0280B-S2	<p>4MP IR Mini Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux @ F1.6 2.6 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB max IR distance:30 m, Smart IR IP67, IK10, PoE</p>		45.100.000
				
76	HDW2431TP-AS-0280B-S2	<p>4MP Lite IR Fixed-focal Eyeball Network Camera 1/3" CMOS image sensor, Outputs 4MP (2560 × 1440)@25/30 fps H.265 coding, SMART H.264+/H.265+, Fixed Lens 2.8mm Min. Illumination 0.008 Lux @ F1.6 WDR(120dB), 3D NR, HLC, BLC, digital watermarking, Intelligent detection: Intrusion, tripwire Max. 256 GB SD card and built-in Mic, 12V DC/POE/IP67</p>		47.600.000
				
77	HDW2431TMP-AS-0280B-S2	<p>4MP WDR IR Eyeball Network Camera, Starlight 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.6 2.8 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, Built in Mic max IR distance:30 m, Smart IR IP67, PoE</p>		48.400.000
				
78	HDBW1431EP-0280B-S4	<p>4MP Entry IR Fixed-focal Dome 1/3" CMOS image sensor Network, low illuminance Min. Illumination : 0.03 Lux @ F2.0 ,Illumination Distance : 30 m(3 IR LED), S/N Ratio &gt; 56dB Lens Fixed-focal 2.8 mm , Horizontal: 93° / Vertical: 53° / Diagonal: 111° Smart H.265+, H.265, Smart H.264+, H.264 Main Stream: 2688 × 1520 (20 fps) , high compression rate, ultra-low bit rate WDR (120dB), 3D DNR, HLC, BLC, AWB, AGC, ROI(4 years), Smart Illumination Storage(FTP, SFTP, NAS) , ROM : 128MB, RAM : 512MB 12V DC/POE (802.3af), Power Consumption &lt; 5.5W, 1 port RJ-45 (10/100 Base-T) ,IP67, IK10</p>		41.250.000
79	HDW1431TIP-A-0360B-S4	<p>4MP Entry IR Fixed-focal Eyeball Network Camera 1/3"4Megapixel progressive CMOS, Fixed-focal 3.6mm 20fps@4.1M(2688×1520) &amp; 25fps@4M(2560×1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), Image flip, 3D DNR, HLC, BLC, digital watermar Support ROI,Built-in MIC Max. IR LEDs Length 30m, IP67, PoE</p>		41.700.000
				
80	HDW1431TIP-0280B-S4-S5	<p>4MP Entry IR Fixed-focal Eyeball Network Camera 1/3"4Megapixel progressive CMOS 20fps@4.1M(2688×1520) &amp; 25fps@4M(2560×1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Support ROI Max. IR LEDs Length 30m, IP67, PoE</p>		37.400.000
81	DH-IPC-HDW2249TP-S-IL-0280B	<p>2MP Smart Dual Illumination Fixed-focal Eyeball WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance Min. Illumination : 0.0002 lux@F1.6 (B/W, 30 IRE) , Fixed Lens 2.8 mm Outputs max. 2 MP (1920 × 1080)@25/30 fps Smart Codec : Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B SMD Plus, Intrusion, tripwire (accurate detection of vehicle and human). Supports max. 256G Micro SD card, <b>built in MIC</b>. ROI, WDR, 3D NR, HLC, BLC, digital watermarking Built-in warm light/IR LED : 30m/30m 12 VDC/PoE power supply, easy for installation, IP67</p>		45.100.000
				

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
82 HDW2231TMP-AS-S2	<p>2MP WDR IR Eyeball Network Camera, <b>Starlight</b>            1/2.8" 2Megapixel progressive CMOS            Min. Illumination:0.002 Lux@F1.6            Outputs max. 2MP (1920 × 1080) @25/30 fps            2.8mm Fixed lens            SMART H.264/H.265 dual-stream encoding            IVS(Tripwire, intrusion)            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Rol            Built-in Mic, Micro SD memory 256GB            Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p>		38.500.000
83 IPC-HDW2231TP-AS-0280B-S2	<p>2MP Lite IR Fixed-focal Eyeball Network Starlight Camera            2MP, 1/2.8" Progressive CMOS            low illuminance 0.002 Lux @F1.6            high image definition 2MP@25/30fps            2.8mm fixed lens            SMART H.264+/H.265+            IVS Intrusion/Tripwire            WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch            Micro SD 256GB, Built-in Mic            12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T</p>		37.950.000
84 IPC-HDW2230T-AS-S2	<p>2MP IR Eyeball Network Camera            2MP, 1/2.7" Progressive CMOS            low illuminance 0.005 Lux @ F1.6            high image definition 2MP@25/30fps            2.8mm fixed lens            SMART H.264+/H.265+            IVS Intrusion, Tripwire            Micro SD 256GB, Built-in Mic            DWDR, 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch            12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T</p>		33.000.000
85 IPC-HDBW2230E-S-S2	<p>2MP Lite IR Fixed-focal Dome Network Camera            2MP, 1/2.7" Progressive CMOS            low illuminance 0.005` Lux @F1.6            high image definition 2MP@25/30fps            2.8mm Fixed Lens            SMART H.264+/H.265+            IVS Tripwire; intrusion            Micro SD 256GB            DWDR, 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch            12V, PoE, IP67, 3 IR LEDs 30m Distance, Onvif Profile S/G/T</p>		32.800.000
86 HDW1530TP-0280B-S6	<p>5MP Entry IR Fixed-focal Eyeball Network Cam            1/2.7" CMOS image sensor            low illuminance 0.003 Lux @F2            Outputs max. 5MP (2880 × 1620) @20            H.265 code, SMART H.264 +/H.265            DWDR, 3D NR, HLC, BLC, digital watermarking            Built-in MIC,12 V DC/PoE power supply</p>		44.600.000
87 DH-IPC-HDW1239T1-A-LED-S5	<p>2MP Lite Full-color Fixed-focal Eyeball Network Camera            Outputs max. 2MP (1920 × 1080) @25/30 fps            2.8mm fixed lens            H.265 codec, high compression rate, ultra-low bit rate            Min. Illumination : 0.005 Lux @F1.6,            Built-in LEDs, max LED distance: 15 m, <b>built in MIC</b>            ROI, SMART H.264/H.265, flexible coding, applicable to various            Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking,            12V DC/PoE power support, IP67 protection</p>		33.000.000
88 DH-IPC-HDW1239T1-LED-0360B-S5	<p>2 MP Entry Full-color Fixed-focal Bullet Network Camera            2MP, 1/2.8" Progressive CMOS            low illuminance 0.005 Lux @F1.6            high image definition 2MP@25/30fps            3.6mm fixed lens            Smart H.265+/Smart H.264+            DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination            12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T</p>		29.100.000
89 DH-IPC-HDW1239T1P-LED-0280B-S5	<p>2 MP Entry Full-color Fixed-focal Bullet Network Camera            2MP, 1/2.8" Progressive CMOS            low illuminance 0.005 Lux @F1.6            high image definition 2MP@25/30fps            2.8mm fixed lens            Smart H.265+/Smart H.264+            DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination            12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T</p>		29.100.000
90 DH-IPC-HDW1230T1-A-S5	<p>2MP Entry IR Fixed-Focal Eyeball Network Camera            Outputs max. 2MP (1920 × 1080) @25/30 fps            2.8mm fixed lens            H.265 codec, high compression rate, ultra-low bit rate, Min. Illumination : 0.01 Lux @F2.0            Built-in efficient IR illuminator, and the max. illumination distance is 30 m            ROI, SMART H.264+/H.265+, flexible coding, applicable to various, <b>built in MIC</b>            Rotation mode, DWDR, 3D NR, HLC, BLC, S/N Ratio 56 dB, digital watermarking            12V DC/PoE power supply, IP67 protection</p>		31.700.000










ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
91	HDW1230T1P-0280B-S5	2MP Entry IR Fixed-Focal Eyeball Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0, 2.8 Fixed lens DWDNR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI, EIS max IR distance:30 m, Smart IR, IP67, PoE		26.400.000
92	HDBW1230EP-0360B-S2	1/2.7" 2Megapixel progressive scan CMOS, 3.6mm fixed lens H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDNR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, IK10, PoE		29.700.000
93	DH-SD29204T-GN	1/2.7" 2MP CMOS Sensor, 2.7mm ~ 11mm , 4x Optical Zoom H.264+/H.264 Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 100°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in Mic, IR Distance up to 30m, POE, (Tripwire Intrusion   Scene Change   Face   Abandoned-Missing Object)		79.750.000
94	DH-SD1A203T-GN	1/2.8" 2MP STARVIS™ CMOS (Starlight) H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 25/30fps@1080P, 2.7mm ~ 8.1mm , 3x Optical Zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max Pan: 80° /s; Tilt: 40° /s speed Pan: 0° ~ 355°; Tilt: 5° ~ 90° rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern, Support Defog, IR Distance up to 15m, IP 66, support POE (Tripwire Intrusion Abandoned Missing Face Detection)		81.400.000
95	SD3A205-GNP-PV	2MP Starlight IR AI WizSense Network PTZ Camera H.265; H.264B; H.264M; H.264H; MJPEG; MJPEG (Sub Stream); H.265+; H.264+ Focal Length 2.7 mm~13.5 mm, Optical Zoom 5x Tripwire and intrusion, Deep-learning-based perimeter protectionm SMD Plus IR distance up to 30m Starlight technology Up to 300 presets DWDNR, HLC, BLC, AGC, AWB, 2D/3D DNR, Day/Night Auto (ICR), ROI, Defog Built-in Mic, Built-in Speaker, Two Way Audio ONVIF Profile S&G&T; CGI IP66; TVS 2000V lightning proof; surge protection; voltage transient protection		106.200.000
96	DH-SD6CE230U-HNI	1/2.8" 2MP STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P 4.5mm~135mm Powerful 30x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC Auto-tracking, Tripwire, Intrusion, Abandoned/Missing, Face Detection, Heat Map), Support Defog, ROI, EIS Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Alarm 7/2 in/out, Audio 1/1 in/out, 1* Video output RS485, IR Distance up to 200m, PoE+, IP67, IK10		374.000.000
97	DH-SD6CE245XA-HNR	2MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6) Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length 45x optical zoom WDR(120dB), Day/Night(ICR), 2D/3D DNR, BLC, HLC, AGC, AWB Auto-tracking, Perimeter protection, Face detection, SMD Plus Tripwire and intrusion, alarm triggering by target types (human and vehicle) Support Defog, ROI Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan 1* Video output, Rs485 7/2 Alarm in/out, 1/1 Audio in/out IR Distance up to 250m, PoE+, IP67, IK10		528.000.000
98	DH-SD6CE245U-HNI	2MP 45x Starlight IR PTZ Network Camera 1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6) Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length 45x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC, AGC, AWB Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection, Heat Map) Support Defog, ROI, EIS Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan 1* Video output, Rs485 7/2 Alarm in/out, 1/1 Audio in/out IR Distance up to 250m, PoE+, IP67, IK10		Call

99	SD5A245XA-HNR		<p>2MP 45x Starlight IR WizSense Network PTZ Camera                      1/2.8" 2Megapixel STARVIS™ CMOS                      H.265; H.265+; H.264+; H.264; MJPEG (Sub Stream)                      Max. 50/60 fps@1080P                      Pan/Tilt Range Pan: 0°-360°; Tilt: -15°-+90°                      Manual Control Speed Pan: 0.1°/s-240°/s; Tilt: 0.1°/s-120°/s                      WDR(120db), HLC, BLC, 2D/3D DNR, Rol, EIS, Defog, AWB, AGC, Privacy Masking, Day/Night Auto                      Auto Tracking, SMD Plus, Intrusion, Tripwire, Object Abandoned/Missing, Face Detection                      Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan                      Alarm I/O 2/1, Audio I/O 1/1, Supports Two Way Talk                      Focal Length 3.95 mm-177.7 mm, Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0 Lux (IR on)                      IR distance up to 150 m, 45x optical zoom                      ONVIF Profile S&amp;G&amp;T, DC 24V/2.5A ± 25%; PoE+ (802.3at), Operating Temperature -40°C to +70°C                      IP67; IK10; TVS 6000V lightning protection; surge protection; voltage transient protection</p>		517.000.000
100	DH-SD5A232XB-HNR		<p>2MP 32x Starlight IR WizSense Network PTZ Camera                      1/2.8" 2Megapixel STARVIS™ CMOS                      32x optical zoom, Max. 50/60 fps@2M                      Min Illumination Color: 0.005 lux@F1.6, Focal Length 4.8 mm-154 mm                      Smart H.265+; H.265; Smart H.264+; H.264B                      Face detection, tracking and perimeter protection, SMD PLUS                      IR distance up to 150 m, PoE+, IP67, IK10                      WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC</p>		448.000.000
101	DH-SD5A232XA-HNR	 	<p>1/2.8" 2Megapixel STARVIS™ CMOS                      H.265+/H.265/H.264+/H.264 Triple-streams encoding                      Max. 50/60fps@1080P, 4.9mm~156mm 32x optical zoom                      Max 400°/s pan speed, 360° endless pan rotation                      WDR(120dB), Day/Night(ICR), Ultra DNR(2D/3D), BLC, HLC                      Support Defog, ROI, Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection)                      Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan                      Alarm 2/1 in/out, Audio 1/1 in/out                      IR Distance up to 150m, PoE+, IP67, IK10</p>		448.000.000
102	DH-SD49425ZB-HNR	 	<p>4MP 25x Starlight IR WizSense Network PTZ Camera, Image Sensor: 1/2.8" STARVIS™ CMOS                      1/2.8" 4Megapixel CMOS, Powerful 25x optical zoom, ROM: 4GB, RAM: 1GB                      Starlight technology, Max.25/30fps@4M, Illuminator Number: 4                      Focal Length: 4.8 mm-120 mm, Field of View: H: 60.0°-2.5°; V: 30.8°-2.2°; D: 66.7°-2.9°                      Min. Illumination: Color: 0.005Lux@F1.6, B/W: 0.0005Lux@F1.6: 0Lux@F1.6 (IR light on)                      Illuminator On/Off Control: Zoom Prio/Manual/SmartIR                      Perimeter protection, Face Detection, Smart Capture, SMD PLUS, IVS: Object Abandoned/Missing                      Support PoE+, IR distance up to 100m, BLC, WDR 120db, HLC, AGC, ANR, ROI, Electronic Defog                      Pan: 0.1°-200°/s, Tilt: 0.1°-120°/s, Presets: 300, Tour: 8 (up to 32 presets per tour), Pattern: 5, Scan: 5                      IP66, DC 12V/3A, PoE+ (802.3at) Audio Input: 1, Audio Output: 1, Alarm I/O: 2/1</p>		294.000.000
103	SD49425XB-HNR		<p>4MP 25x Starlight IR WizSense Network PTZ Camera                      1/2.8" STARVIS™ Progressive CMOS                      H.265+/H.265/H.264+/H.264/MJPEG (sub stream)                      Max.25/30fps@4M, 960P, 720P                      4.8mm~120mm 25x optical zoom                      Max 240°/s pan speed, 360° endless pan rotation                      WDR(120db), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus                      IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest)                      False Alarm Avoidance for Animals, Leaves, Bright Light                      Support Defog and EIS                      Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan                      Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</p>		294.000.000
104	SD49225XA-HNR-S3		<p>2MP 25x Starlight IR WizSense Network PTZ Camera                      1/2.8" 2Megapixel STARVIS™ CMOS,                      25x optical zoom, Min Illumination Color: 0.005 lux@F1.6                      Max. 25/30 fps@1080p                      IR distance up to 100 m, Perimeter protection, Face detection, SMD Plus, IP66                      Pan: 0° to 360° endless, Tilt: -15° to +90°, auto flip 180°, Pan: 200°/s; Tilt: 100°/s                      Smart H.265+; H.265; Smart H.264+; H.264B; H.264M; H.264H; MJPEG (Sub Stream)                      Tripwire and intrusion. Support alarm triggering by target types (human and vehicle)                      WDR(120db), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC</p>		242.000.000

105	SD49225XA-HNR	 <p>2MP 25x Starlight IR PTZ AI Network Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max. 1~60fps@1080P,960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</p>		242.000.000
106	SD49225DB-HNY	<p><b>NEW</b></p> <p>2MP 25x Starlight IR Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom - Focal Length 4.8 mm~120 mm Max. 25/30 fps@1080p Min. Illumination Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 lux (IR light on) Illumination Distance 100 m (328.08 ft) (IR) Max. Aperture F1.6~F3.5 Smart IR - 4 IR - S/N Ratio ≥ 55 dB IVS (Perimeter Protection) : Tripwire , intrusion / SMD Plus / Face Detection / Motion Detection Smart H.265+;H.265;Smart H.264+;H.264;H.264B;MJPEG(Sub Stream) WDR 120db, Day/Night Auto (ICR)/Color/B/W, HLC, BLC, AWB, AGC, 2D DNR, 3D DNR, Roi, EIS, Defog Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm in/out 2/1, Audio in/out 1/1, 12 VDC/3 A, PoE+, IP66, FTP/ Micro SD card (512 GB)/ NAS</p>		242.000.000
107	SD49225ZB-HNR	<p>1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom - Focal Length 4.8 mm~120 mm Max. 25/30 fps@1080p Min. Illumination Color: 0.005 lux@F1.6 / B/W: 0.0005 lux / 0 lux (IR light on) Illumination Distance 100 m (328.08 ft) (IR) Max. Aperture F1.6~F3.5 Smart IR - 4 IR - S/N Ratio ≥ 55 dB IVS (Perimeter Protection) : Tripwire , intrusion / SMD Plus / Face Detection / Motion Detection Smart H.265+; H.265; Smart H.264+ WDR 120db, Day/Night Auto (ICR)/Color/B/W, HLC, BLC, AWB, AGC, 2D DNR, 3D DNR, Roi, EIS, Defog Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm I/O : 2/1 - IP66 - Power Supply 12 VDC, 3 A - PoE+ Storage : FTP/ Micro SD card (512 GB)/ NAS</p>		242.000.000
108	SD59430U-HNI	<p>1/3" CMOS Sensor H.265+/H.265/H.264+/H.264 Encoding, Ultra-low bit rate Max. 25/30fps@4M(2592x1520) &amp; 50/60fps @1080P resolution WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 4.5mm ~ 135.0mm , 30x Optical Zoom Max 400°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Micro SD card memory , 64 GB Audio In/Out, Alarm In/Out, IP66, POE+ IR Distance up to 100m(AC24V)/ 80m(DC12V) Smart Detection (Tripwire Intrusion   Scene Change   Face   Anondoned-Missing Object)</p>		385.000.000
109	SD5A432XB-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.6, 0 Lux (IR on) 4.8 mm~154 mm Powerful 32x optical zoom, Max. Aperture F1.35~F4.4 Support human, motor vehicle and non-motor vehicle image capture Tripwire and intrusion. Support alarm triggering by target types (human and vehicle) Support filtering false alarms caused by animals, rustling leaves, bright lights, etc. Pan: 0° to 360° endless , Tilt: -15° to +90°, auto flip 180° , Pan: 0.1°~300°/s , Tilt: 0.1°~200°/s WDR(120), EIS, Defog, Roi,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Alarm I/O : 2/1 , Audio I/O : 1/1 ,PoE+ ,IP67; IK10; TVS 6000 V</p>		484.000.000
110	DH-SD5A432GB-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera Image Sensor 1/2.8" CMOS, Max. Resolution 2560 (H) × 1440 (V) Electronic Shutter Speed 1/1 s~1/30,000 s, Min. Illumination, Color: 0.005 lux@F1.6, B/W: 0.0005 lux@F1.6 Illumination Distance 150 m(IR), Focal Length 4.8 mm~154 mm Manual Control Speed Pan: 0.1°/s~300°/s, Tilt: 0.1°/s~200°/s Preset 300, Tour 8 (up to 32 presets per tour), Pattern 5, Scan 5 Perimeter Protection, Face Detection, Auto Tracking, Quick Pick, SMD BLC, WDR 120 db, WB, AGC, ANR, Roi, EIS, Defog Electronic, S/N Ratio ≥55 dB Storage : FTP, Micro SD card (512 GB); NAS, Alarm I/O 2/1, Audio I/O 1/1 Power Supply 24 VDC, 2.5 A (± 25%), Operating Temperature -40 °C to +70 °C</p>		506.000.000



111	SD5A432XA-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.35, 0 Lux (IR on) 4.9 mm–156 mm Powerful 32x optical zoom, Max. Aperture F1.35–F4.4 Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°–360° endless rotation WDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&amp;G&amp;T IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection; voltage transient protection</p>		471.000.000
112	SD5A445GB-HNR	<p><b>NEW</b></p> <p>4MP 45x Starlight IR Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.264H; H.264B; Smart H.265+; H.264; H.265; MJPEG(Sub Stream); Smart H.264+ Min. Illumination Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 lux (IR light on) 3.95 mm–177.75 mm 45x optical zoom Starlight technology IR distance up to 150 m WDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Perimeter protection, Face detection, SMD 4.0, Quick Pick, Auto-tracking 3.0 Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm in/out 2/1, Audio in/out 1/1, IP67, IK10, TVS 6000V lightning proof; surge protection; voltage transient protection</p>		605.000.000
113	SD5A445XA-HNR-1T	<p>4MP 45x Starlight IR DHOP Network PTZ Camera - Max. 25/30 fps@4MP 1/2.8" 4Megapixel STARVIS™ CMOS - Progressive CMOS - ROM : 4GB - RAM : 1GB 1T computing power for enhanced performance - Flash : 350 M - Memory : 300 M Compression H.265/H.265+/H.264+/H.264/MJPEG(Sub Stream) Min. Illumination Color: 0.005 Lux@F1.6 / B/W: 0.0005 Lux@F1.6 / 0 Lux (IR light on) Starlight technology - Illumination Distance : 150 m (492.13 ft) - Illuminator Number : 4 Focal Length 3.95 mm–177.7 mm - Max. Aperture F1.6–F4.95 - Field of View H: 70.3°–1.8°; V: 37°–1° Pan: 0°–360°; Tilt: –15° +90° / Manual Control Speed : Pan: 0.1°/s–300°/s; Tilt: 0.1°/s–200°/s Preset Speed : Pan: 400°/s; Tilt: 300°/s - Presets : 300 - Tour 8 (up to 32 presets per tour) - Pattern : 5 WDR(120), HLC, BLC, AWB, AGC, 2D DNR, 3D DNR, ROI, EIS, Electronic Defog Alarm I/O 2/1 - Audio I/O 1 (Line in; bare wire)/1 (Line out; bare wire) - 1 RJ-45 Port 10/100Base-T DC 24 V/2.5 A ± 25% - PoE+ (802.3at), 11 W / 20 W (IR light on) IP67, IK10</p>		588.500.000
114	SD5A445XA-HNR	<p>4MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265/H.265+/H.264+/H.264/MJPEG(Sub Stream) 3 Streams, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0Lux (IR light on) 3.95 mm–177.7 mm Powerful 45x optical zoom Max. Aperture F1.6–F4.95 Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°–360° endless rotation WDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&amp;G&amp;T IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection</p>		588.500.000
115	SD6CE445XA-HNR	<p>4MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+/H.265/H.264+/H.264/MJPEG(Sub Stream) Max. 25/30fps@4MP Minimum Illumination Color: 0.005 Lux@F1.6; B/W: 0.0005 Lux@F1.6; 0 Lux@F1.6 (IR on) 3.95 mm–177.75 mm Powerful 45x optical zoom Max. Aperture F1.6–F4.95 Pan/Tilt Range Pan: 0°–360° endless; Tilt: -20°–90°, auto flip 180° Preset Speed Pan: 300°/s; Tilt: 200°/s WDR 120db, BLC, HLC, Auto ICR, AWB, AGC, 2D/3D DNR, Rol, EIS, Defog Deep-learning-based auto tracking and perimeter protection Face detection, SMD Plus, Tripwire, Intrusion, Human/Vehicle/Motor-non Motor Vehicle Detection Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 7/2 Alarm I/O, ONVIF Profile S&amp;G&amp;T IR distance up to 250m, DC 24 V/2.5 A, PoE+, IP67, IK10</p>		616.000.000
116	DHI-NVR1104HS-S3/H (V2.0)	<p><b>4K</b></p> <p>4 Channel IPC Input, 4K Lite H.265 NVR 1/4 Live &amp; Playback Smart H.265+/Smart H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60Mbps for forwarding. Up to 8MP Resolution for Preview &amp; Playback Decoding Capacity : 1–ch@8MP(30FPS) or 1–ch@5MP(30FPS) or 2–ch@4MP(30FPS) or 2–ch@3MP(30FPS) or 4–ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P 1 SATA 2.0 port, up to 8TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ–45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)</p>		31.350.000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
117	<p>NVR2104HS-P-I</p> <p><b>Wiz Sense</b></p> <p>4 Channel Compact 1U 4PoE WizSense Network Video Recorder, New 4.0 user interface H.264/H.265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch 1 VGA/1 HDMI simultaneous video output, HDMI 4K, non-simultaneous video output is also supported on 1080p 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images Max. decoding capability: 4x1080P@30fps. Supports adaptive decoding Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding Resolution 12M/8M/5M/4M/3M/2M/720P/D1 AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps 4 PoE Ports, 1 SATA port, up to 8 TB, 1 front USB 2.0 port, 1 rear USB 2.0 port, 1 RJ-45 port (10/100 Mbps), 4 RJ-45 ports with PoE power supply (10/100 Mbps)</p>		66.000.000
118	<p>NVR2104HS-4KS2</p> <p><b>4K</b></p> <p>4 channel IP camera input H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&amp;playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		35.750.000
119	<p>NVR2104HS-P-4KS2</p> <p><b>4K</b></p> <p>4 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&amp;playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 4PoE Port, P2P support</p>		46.800.000
120	<p>DHI-NVR1108HS-S3/H</p> <p><b>4K</b></p> <p>8 Channel IPC Input, 4K Lite H.265 NVR 1/4/8/9 Live &amp; Playback Smart H.265+/Smart H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding. Up to 8MP Resolution for Preview &amp; Playback Decoding Capacity : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P 1 SATA 2.0 port, up to 8TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)</p>		38.400.000
121	<p>NVR2108HS-4KS2</p> <p><b>4K</b></p> <p>8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&amp;playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		44.000.000
122	<p>NVR2108HS-8P-4KS2</p> <p><b>4K</b></p> <p>8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&amp;playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 8Port PoE, P2P support</p>		62.200.000
123	<p>NVR2108HS-S3</p> <p><b>4K</b></p> <p>8 Channel Lite Series, Compact 1U 1HDD Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 decoding format Max. decoding capability: 6 x 1080p@30 fps. Supports adaptive decoding AI by camera: perimeter protection, and SMD Plus Multi-channel Playback Up to 8 channels, HDD Interface 1 SATA port, up to 16 TB Audio Input/Out : 1/1 , Network Port 1 x RJ-45, 10/100 Mbps Power Supply 12 VDC, 1.5 A</p>		51.200.000
124	<p>NVR2108HS-I2</p> <p><b>Wiz Sense AI</b></p> <p>8 Channel Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. decoding capability: 6 x 1080p@30 fps. Supports adaptive decoding 1-channel face detection and recognition (AI by NVR) 1-channel perimeter protection (AI by NVR), 4-channel SMD Plus (AI by NVR) AI by camera: Face detection and recognition, perimeter protection, and SMD Plus HDD 1 SATA port, up to 10 TB, RCA Input 1, RCA Output 1 Power Supply 12 VDC, 1.5 A, Operating Temperature -10 °C to +55 °C</p>		63.800.000
125	<p>NVR2108HS-I</p> <p><b>12MP</b></p> <p><b>Wiz Sense AI</b></p> <p>8 Channel 12MP WizSense NVR 1/4/8 Live &amp; Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled : 1ch 8MP@30fps or 1ch 5MP@30fps or 2ch 4MP@30fps or 4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 1 SATA II port, up to 8TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		63.800.000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
126 NVR4108HS-4KS2	<p>8 channel IP camera input 1/4/8/9 channel Live Preview, 8CH Playback H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB 2.0 100 Mbps Network Card, P2P support</p>		51.700.000
127 DHI-NVR2216-4KS2	<p>16 Channel 4K Lite H.265 NVR 1/4 Live &amp; Playback Dual-core embedded processor, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth, Up to 1ch@8MP/4ch@1080p decoding HDMI/VGA simultaneous video output 2 SATA III Ports, up to 6TB capacity for each, Total 12TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (1000Mbps), P2P Support</p>		68.200.000
128 NVR2116HS-I	<p>16 Channel 12MP WizSense NVR 1/4/9/16 Live &amp; Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 1 SATA II port, up to 8TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		80.300.000
129 NVR2116HS-I2	<p>16 Channel Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Network Bandwidth: Ai off: Access: 144 Mbps; Storage: 144 Mbps; Forward: 72 Mbps Ai on: Access: 72 Mbps; Storage: 72 Mbps; Forward: 36 Mbps Resolution: 12MP; 8MP; 5MP; 4MP; 3MP; 2MP; 720p; D1 Decoding Capability: Ai disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps Ai enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps 1 x VGA, 1 x HDMI (simultaneous) 4K Output 1-channel face detection and recognition (Ai by NVR); 1-channel perimeter protection (Ai by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus (Ai by NVR); Ai by camera: Face detection and recognition, perimeter protection, and SMD Plus 1 SATA II port, up to 10TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		79.200.000
130 DHI-NVR2216-I	<p>16 Channel 12MP WizSense NVR 1/4/9/16 Live &amp; Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 2 SATA 2.0 port, up to 8TB each, Total 16TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		102.500.000
131 DHI-NVR2216-I2	<p>16 Channel 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. decoding capability: 6 x 1080p@30 fps. Supports adaptive decoding Ai by NVR: 1-channel face detection and recognition; 1-channel perimeter protection; up to 10 face databases and 5,000 face images; 4-channel SMD Plus Ai by camera: Face detection and recognition, perimeter protection, and SMD Plus 2 SATA each up to 10TB, 2 USB, 1 HDMI, 1 VGA, 1 LAN 1000Mbps, Audio in/out 1/1, Onvif (S, T, G)</p>		102.500.000
132 NVR4116HS-4KS2	<p>16 Channel Compact 1U 4K&amp;H.265 Lite Network Video Recorder Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch Max 80Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback 8-channel decoding@1080p (30 fps) Ai by Camera: Perimeter protection; SMD Plus; people counting; heat map target classification (human, vehicle) HDMI(4K)/VGA simultaneous video output 1 SATA III port, up to 10 TB, 1 front USB 2.0 port, 1 rear USB 3.0 port Audio I/O 1/1 for Two Way Talk Only 100 Mbps Network Card, P2P support</p>		76.000.000




مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
133 NVR4116HS-4KS2/L	<p>16 channel IP camera input, 16 channel Live Preview Smart H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback 16-ch@720P decoding capacity Support SMD Plus by Camera HDMI(4K)/VGA simultaneous video output Support 1 SATA HDD up to 8TB, 2 USB2.0 100 Mbps Network Card, P2P support</p> <p><b>4K</b></p>		76.000.000
134 NVR4216-4KS2/L	<p>16 channel IP camera input, 16 channel Live Preview Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding 8-ch@1080P decoding capability HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with Face Attributes, perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)</p> <p><b>4K</b> <b>UPGRADED</b></p>		102.500.000
135 NVR4216-16P-4KS2/L	<p>16 channel IP camera input, 16 channel Live Preview Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding 8-ch@1080P decoding capability HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with Face Attributes, perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 × front USB2.0, 1 × back USB2.0) 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, 16 Port PoE, ONVIF(profile T/S/G)</p> <p><b>4K</b> <b>UPGRADED</b></p>		166.000.000
136 NVR4216-4KS3	<p><b>NEW</b></p> <p>16CH 1U 2HDDs Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats Max. 160/160Mbps incoming/recording bandwidth Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps HDMI(4K)/VGA simultaneous video output AI by Recorder supports 4-channel SMD Plus AI by Camera supports face detection(6CHs) and recognition(6CHs), perimeter protection(6CHs), SMD Plus(6CHs), people counting, stereo analysis and heat map Supports IP cameras with a resolution up to 12MP 2 SATA ports. Each disk up to 20TB, Audio in/out 1/1 for Two Way Talk, Alarm in/out 4/2, USB 2 Ports, LAN 1*1000, P2P support, ONVIF(profile T/S/G)</p> <p><b>4K</b> <b>AI</b></p> <p><b>NEW VERSION</b> <b>NEW VERSION</b> <b>NEW VERSION</b></p>		102.500.000
137 NVR4232-EI	<p><b>NEW</b></p> <p>32CH 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled) Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding HDMI(4K)/VGA simultaneous &amp; independent video output AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus AI by Camera: Face detection(8CHs) and recognition(8CHs), perimeter protection(8CHs); SMD Plus(8CHs); people counting; stereo analysis; heat map Supports IP cameras with a resolution up to 16MP 2 SATA ports, up to 16TB., Audio in/out 1/1 for Two Way Talk, Alarm in/out 4/2, USB 2 Ports, LAN 1*1000, P2P support, ONVIF(profile T/S/G)</p> <p><b>4K</b> <b>AI</b></p> <p><b>Wiz Sense</b></p>		146.500.000
138 NVR4232-4KS2/L	<p>32 Channel 1U 2HDDs Network Video Recorder Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with attributes, perimeter protection, IVS, people counting, heat map, and SMD, Human &amp; Vehivle Classification 2 SATA III ports, up to 10 TB each port, 1 × front USB2.0; 1 × back USB2.0 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)</p> <p><b>4K</b> <b>AI</b></p>		121.000.000
139 NVR4232-4KS2	<p>32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*1000Mbps Network Card, P2P support</p> <p><b>4K</b></p>		119.000.000
140 NVR4432-4KS2/I	<p>32 Channel 1.5U 4HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Access, storage or forwarding at 256 Mbps, Max. decoding capability: 10 × 1080p@30 fps Face detection; face recognition; perimeter protection,SMD Plus Multi-channel Playback Up to 16 channel The maximum HDD capacity 4 SATA ports, up to 10 TB Alarm Input 16,Alarm Output 4 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet port</p> <p><b>4K</b> <b>AI</b></p> <p><b>Wiz Sense</b></p>		219.000.000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
141 NVR4232-4KS3	<p><b>NEW</b></p> <p>32CH 1U 2HDDs Lite Network Video Recorder  Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats  Max. 160Mbps incoming bandwidth  Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps  HDMI(4K)/VGA simultaneous video output  AI by Recorder supports 4-channel SMD Plus  AI by Camera supports face detection(6CHs) and recognition(6CHs), perimeter protection(6CHs), SMD Plus(6CHs), people counting, stereo analysis and heat map  Supports IP cameras with a resolution up to 12 MP  2 SATA ports. Each disk up to 20TB, Audio in/out 1/1 for Two Way Talk, Alarm in/out 4/2, USB 2 Ports, LAN 1*1000, P2P support, ONVIF(profile T/S/G)</p>		123.200.000
142 DHI-NVR5232-4KS2(V2.0)	<p>32Channel 1U 4K &amp; H.265 Pro Network Video Recorder (V2.00)  Smart H.265+/H.265/H.264+/H.264/MJPEG decoding  Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview &amp; playback  Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding  1*HDMI(4K)/1*VGA simultaneous video output  2*SATA HDDs(10 TB for each HDD), 2 USB(1 USB3.0,1 USB2.0)  1*1000 Mbps Network Card, RS232, RS485,4/2 Alarm In/out , P2P Support</p>		214.500.000
143 NVR5232-EI	<p><b>NEW</b></p> <p>32 Channels 1U 2HDDs WizSense Network Video Recorder  Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format  Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps  Max. 384 Mbps incoming/recording/outgoing bandwidth  16ch AcuPick, N+M Clustering, Face Detection, Face Recognition, Face Attributes, Face Expression, SMD Plus, Perimeter Protection, Metadata, ANPR, Stereo Analysis, Heatmap, People Counting  AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.  AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting  Audio in/out 1/1, Alarm in/out 4/2, 2 SATA each up to 16TB, RS232, RS485, 2 USB 3.1 USB 2.1, HDMI 1 VGA, 1 LAN</p>		238.700.000
144 NVR5432-EI	<p><b>NEW</b></p> <p>32 Channels 1.5U 4HDD WizSense Network Video Recorder  Industrial-grade processor - Embedded Linux OS  Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format  Max. 384 Mbps incoming/recording/outgoing bandwidth  AI by recorder: 2ch face detection and recognition, 4ch perimeter protection, and 8ch SMD Plus  AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting  Network Port 2 (10/100/1000 Mbps Ethernet port, RJ-45)  4 SATA ports, up to 16 TB - Security baseline 2.3 - Supports 4K display - Alarm In/Out : 16ch/6ch</p>		330.000.000
145 NVR5432-4KS2(V2.0)	<p>32Channel 1.5U 4K &amp; H.265 Pro Network Video Recorder (V2.00)  Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding  Max 320Mbps incoming bandwidth  Up to 12Mp resolution preview &amp; playback  Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding  2*HDMI/2*VGA simultaneous video output  4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0)  Support 1 e-SATA, 2*1000 Mbps Network Card  RS232, RS485,16/6 Alarm In/out , P2P Support</p>		280.500.000
146 NVR5832-EI	<p><b>NEW</b></p> <p>32 Channels 2U 8HDD WizSense Network Video Recorder  Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format  Max. 384 Mbps incoming/recording/outgoing bandwidth  Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps  Support AcuPick with Max. 16-Channel, Support N+M cluster  AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.  AI by camera: Face detection(16CHs) and recognition(16CHs), perimeter protection(16CHs), SMD Plus(16CHs), metadata(8CHs), ANPR(8CHs), stereo analysis, heat map, and people counting  Audio in/out 1/2 for Two way talk only, Alarm in/out 16/8, USB*3, HDMI*2, VGA*2, LAN*2*1000, eSATA*1, 8 SATA Ports each up to 20TB, RS-232, RS-485, P2P Support, Onvif (S/T/G)</p>		506.000.000
147 DHI-NVR5464-4KS2(V2.0)	<p>64Channel 1.5U 4K&amp;H.265 Pro Network Video Recorder (V2.00)  Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding  Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview &amp; playback  Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding  2*HDMI/2*VGA simultaneous video output  4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0)  Support 1 e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out , P2P Support</p>		330.000.000
148 NVR5832-4KS2	<p>32 channel IPC input, 32 Channel Live Preview  H.265/H.264/MJPEG/MPEG4 codec decoding  Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview&amp;playback  Max 16ch@1080P   4ch@4K H.265   H.264 Playback  2HDMI/VGA simultaneous video output  Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0, 2 USB2.0)  2*1000 Mbps Network Card, RS232, 16 Alarm In , 6 Relay Output, P2P Support, Raid 0/1/5/6/10</p>		363.000.000



مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
149 NVR5864-EI	<p><b>NEW</b></p> <p>64 Channels 2U 8HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Industrial-grade processor - Embedded Linux Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps Support AcuPick with Max. 16-Channel - Support N+M cluster - Support Raid0/1/5/6/10 Max. 384 Mbps incoming/recording/outgoing bandwidth AI by recorder: 2-ch face detection and recognition, 4-ch perimeter protection, and 8-ch SMD Plus AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting Security baseline 2.3 - Alarm In/Out : 16/8 - 8 SATA ports, each disk up to 16 TB HDMI:2 - VGA:2 - USB:4 - RS485:2 - RS232:1</p> <p><b>4K AI</b></p>		582.000.000
150 DHI-NVR5864-4KS2(V2.0)	<p>64 Channel 2U 4K &amp; H.265 Pro Network Video Recorder (V2.0) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview &amp; playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 8*SATA HDDs(10 TB for each HDD), 4 USB(2 USB3.0, 2 USB2.0) 1*e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out , P2P Support</p> <p><b>4K</b></p>		484.000.000
151 NVR608-32-4KS2	<p>Intel Dual-core Processor, 32 channel IPC input, 32 Channel Live Preview (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding, Max 384Mbps incoming bandwidth Up to 12Mp resolution preview&amp;playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232 , RS485, 16 Alarm In , 8 Relay Output</p> <p><b>4K</b></p>		412.500.000
152 NVR608-64-4KS2	<p>Intel Quad-core Processor 64 channel IPC input, 32 Channel Live Preview (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16), H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview &amp; playback 2HDMI/VGA simultaneous video output 8 SATA III ports, up to 10 TB for a single HDD,1 eSATA Port Support Raid 0/1/5/6/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16 Alarm In , 8 Relay Output</p> <p><b>4K</b></p>		715.000.000
153 DHI-NVR608H-32-XI	<p><b>NEW</b></p> <p>32 Channels 2U 8HDDs WizMind Network Video Recorder Industrial-grade processor AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing Resolution 32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1 Supports N+M cluster Support Raid0/1/5/6/10 &amp; HDD hot swapping AI by recorder: 4ch face detection and recognition; 8ch metadata; 24ch perimeter protection; 32ch SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, and people counting 2-channel VGA, 4-channel HDMI video output with Simultaneous &amp; Independent Video Mode HDMI1 and HDMI2 is 4K, max. resolution of HDMI3 is 8K, max. resolution of HDMI4 is 1080p Support Smart H.265+; H.265; Smart H.264+; H.264; MPEG4; MJPEG Audio I/O 1/2, Alarm I/O 16/8, HDD 8 SATA Ports 16TB Each, 1 e-SATA Port, 4 USB Ports, 2 Network Ports 10/100/1000</p> <p><b>8K AI</b></p>		737.000.000
154 DHI-NVR608H-64-XI	<p><b>NEW</b></p> <p>64 Channels 2U 8HDDs WizMind Network Video Recorder Industrial-grade processor AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing Resolution 32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1 Supports N+M cluster Support Raid0/1/5/6/10 &amp; HDD hot swapping AI by recorder: 4ch face detection and recognition; 8ch metadata; 24ch perimeter protection; 32ch SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, and people counting 64ch - metadata, ANPR 32ch 2-channel VGA, 4-channel HDMI video output with Simultaneous &amp; Independent Video Mode HDMI1 and HDMI2 is 4K, max. resolution of HDMI3 is 8K, max. resolution of HDMI4 is 1080p Support Smart H.265+; H.265; Smart H.264+; H.264; MPEG4; MJPEG Audio I/O 1/2, Alarm I/O 16/8, HDD 8 SATA Ports 16TB Each, 1 e-SATA Port, 4 USB Ports, 2 Network Ports 10/100/1000</p> <p><b>8K AI</b></p>		1.045.000.000
155 NVR608H-128-XI	<p><b>NEW</b></p> <p>128 Channels 2U 8HDDs WizMind Network Video Recorder Industrial-grade processor AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing Resolution 32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1 Supports N+M cluster Support Raid0/1/5/6/10 &amp; HDD hot swapping AI by recorder: 4ch face detection and recognition; 8ch metadata; 24ch perimeter protection; 32ch SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, and people counting 64ch - metadata, ANPR 32ch 2-channel VGA, 4-channel HDMI video output with Simultaneous &amp; Independent Video Mode HDMI1 and HDMI2 is 4K, max. resolution of HDMI3 is 8K, max. resolution of HDMI4 is 1080p Support Smart H.265+; H.265; Smart H.264+; H.264; MPEG4; MJPEG Audio I/O 1/2, Alarm I/O 16/8, HDD 8 SATA Ports 16TB Each, 1 e-SATA Port, 4 USB Ports, 2 Network Ports 10/100/1000</p> <p><b>8K AI</b></p>		1.463.000.000

156	DHI-NVR608-128-4KS2	<p><b>4K</b></p> <p>128 Channel 2U Ultra 4K H.265 Network Video Recorder (1st Screen: 1/4/8/9/16/25/36, 2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview &amp; playback 2HDMI(different Source)/VGA simultaneous video output Support 8 SATA (8TB for each HDD), 1 eSATA Port Support Raid 0/1/5/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16/8 Alarm In/Output</p>		836.000.000
157	ESS1508C	<p>2U standard 19-inch rack case Connect master device via eSATA or USB 1 eSATA port transmission speed up to 3Gbps 1 USB 3.0 port data transmission higher than normal Powerful R / W performance: read &gt;64MB/s, write &gt;64MB/s ESS1508C: Max support internal 8 SATA HDD up to 48TB Recommended with DVR, NVR connection</p>		127.600.000
158	PFS3006-4ET-36	<p>6-Port Fast Ethernet Switch with 4-Port PoE 4 PoE ports with 10/100 Mbps Base-TX 2 uplink ports with 10/100Mbps Base-TX Port1-4 ≤30W, whole PoE budget ≤36W Support 802.3af and 802.3at standards Operating Temperature: -10°C to +55°C Support 250 m long distance PoE transmission Support PoE watchdog Switching Capacity 1.2 Gbps, Packet Forwarding Rate 0.89 Mpps, MAC Table Size 2K, Jumbo Frame 2048 byte Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3X ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 6kV Differential mode: 4kV</p>		24.800.000
159	PFS3106-4ET-60 (V2.0)	<p><b>PoE2.0</b></p> <p>4-Port PoE Switch (Unmanaged) 4 × RJ-45 10/100 Mbps (PoE) 1 × RJ-45 10/100/1000 Mbps (Uplink) 1 × SFP 100/1000 Mbps (Uplink) Intelligent PoE, Hi-PoE 60W (Orange Port), PoE watchdog, 250 m long distance PoE transmission Wide operating temperature: -30°C to +65°C (-22°F to +149°F) Switching Capacity 6.80 Gbps, Packet Forwarding Rate 3.57 Mpps, Packet Buffer Memory 1 Mbit, MAC Table Size 8K Communication Standard IEEE802.3, IEEE802.3u, IEEE802.3X, IEEE 802.3ab, IEEE 802.3z PoE Standard IEEE802.3af, IEEE802.3at, Hi-PoE, 250 m long distance PoE transmission Static Protection Air discharge: 15kV Contact discharge: 8kV, Thunder-proof Common mode: 4kV Differential mode: 2kV</p>		45.100.000
160	PFS3010-8ET-65	<p>10-Port Fast Ethernet Switch with 8-Port PoE Port 1-8: 8 × RJ-45 10/100 Mbps (PoE) Port 9-10: uplink with 10/100 Mbps Support 802.3af and 802.3at standards Support 250 m long distance PoE transmission Support PoE watchdog Port1-8 ≤30W, whole PoE budget ≤65W Switching Capacity 2.0 Gbps, Packet Forwarding Rate 1.49 Mpps, MAC Table Size 2K, Jumbo Frame 2048 byte ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 6kV Differential mode: 4kV</p>		35.400.000
161	PFS3110-8ET-96 (V2.0)	<p><b>PoE2.0</b></p> <p>10-Port Unmanaged Desktop Switch with 8 Port PoE Port 1-8: 8 × RJ-45 10/100 Mbps (PoE) Port 9: 1 × RJ-45 10/100/1000 Mbps (uplink) Port 10: 1 × SFP 1000 Mbps (uplink) Communication Standard IEEE802.3/IEEE802.3u/IEEE802.3X/IEEE 802.3ab/IEEE 802.3z PoE Standard IEEE802.3af/ IEEE802.3at/ Hi-PoE/ IEEE802.3bt Port 1-2 ≤ 90 W, Port 3-8 ≤ 30W, total ≤ 96 W Intelligent PoE, BT 90W, Long distance PoE, PoE watchdog, Wide working temperature Lightning Protection Air discharge: 8kV Contact discharge: 6kV, ESD Protection Common mode: 4kV Differential mode: 2kV</p>		65.500.000
162	PFS3218-16ET-135	<p>Layer 2 PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 16 × RJ45 10/100 Mbps Port 1-2 ≤ 60W, Port 3-16 ≤ 30W, total ≤ 135W IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z PoE Standard IEEE802.3af, IEEE802.3at, Hi-PoE Intelligent PoE, PD Alive (PoE Watchdog), Long Distance PoE Transmission, Smooth Transmission Wide Working Temperature: -10 to 55°C (14°F to 131°F), VLAN Port Isolation Switching Capacity 7.2 Gbps, Packet Forwarding Rate 5.3568 Mpps, Packet Buffer Memory 4 Mbit, MAC Table Size 8K ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 4kV Differential mode: 2kV</p>		112.200.000
163	PFS3226-24ET-240	<p>Layer 2 PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 24 × RJ45 10/100Mbps Intelligent PoE, PD Alive (PoE Watchdog), Long Distance PoE Transmission, Smooth Transmission Wide Working Temperature: -10 to 55°C (14°F to 131°F), VLAN Port Isolation Port1/2 support Hi-PoE (60W), PoE+, PoE Port 1-2 ≤ 60W, Port 3-24 ≤ 30W, total ≤ 240W IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z PoE Standard IEEE802.3af, IEEE802.3at, Hi-PoE Switching Capacity 8.8Gbps, Packet Forwarding Rate 6.5472 Mpps MAC Table Size 8K ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 4kV Differential mode: 2kV</p>		144.100.000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
164 PFT1300	<p>PoE Extender            1*10/100 Base-T PoE power receiving port            1*10/100 Base-T PoE power supply port, supply power for the next extender            1*10/100 Base-T PoE power supply port, supply power for IPC            Support passive PoE cascade power supply and Ethernet data exchange            Support IEEE 802.3af/at standard power supply IP Camera            able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption &lt;=8W), max transmission distance 300m</p>		7.350.000
165 PFM700	<p>*1 Channel HDMI Transmission Signal            *1080P/1080i/720P/576P/576i/480P/480i Resolution Output Signal , *60M (max)Transmission Distance            *Input voltage DC5V            *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video, signal:support HDMI 1.3</p>		21.000.000
166 NKB1000	<p>Keyboard to Control : Dahua High Speed Dome (all models)            Dahua Standalone DVR , Dahua Network High Speed Dome            Network Video Server, Connection : RS485, RS422, USB, RS232 &amp; Network            Three Dimensional Joystick Control of PTZ Functions            Preset Position, Auto Scan, Auto Pan, Auto Tour &amp; Pattern Control, On-Screen Menu &amp; User Operation Procedure Tips            Connect to SmartPSS via USB</p>		134.500.000



MPCCTV

فروشگاه: خیابان جمهوری، نبش شیخ هادی، مجتمع تجاری یگانه، طبقه همکف، پلاک ۲  
 دفتر مرکزی: میدان توحید، نصرت غربی، خیابان کاظم بیگی، بن بست دوم پلاک ۴، واحد ۳