

## لیست قیمت فروردین ماه محصولات HDCVI داهوا



مدل ردیف

خط ویژه: 021-62999021














www.mipcctv.com














قیمت (ریال)

تصویر




















مشخصات فنی

1	HAC-HFW1509MHP-A-LED-S2	 	<p>5MP Full-color HDCVI Bullet Camera Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens <b>Built-in Mic</b> CVI/CVBS/AHD/TVI Switchable, Support OSD Menu 120 dB true WDR, HLC,HLC-Pro, BLC, 3D DNR, AGC, AWB 2 LEDs 50m Distance, Smart Light, IP67, DC12V</p>		33.350.000
2	HAC-HFW1509TMP-IL-A	 	<p>5MP Smart Dual Illuminators Bullet Camera Max 25 fps@5MP (16:9 video output). 120 dB true WDR, 3D NR. Smart Dual Illuminators, 40 m illumination distance Min. Illumination, 0.001 lux@F1.0 (Color, 30 IRE), 0.0001 lux@F1.0 (B/W, 30 IRE) Super Adapt, Built-in MIC, BLC; HLC; WDR; HLC-Pro 3.6 mm fixed lens (2.8 mm optional). CVI/CVBS/AHD/TVI switchable, IP67, 12 VDC</p>		39.400.000
3	HAC-HFW1509TLM-A-LED	 	<p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens <b>Built-in Mic</b> CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m Distance, Smart Light, IP67, DC12V</p>		31.800.000
4	HAC-HFW1509TLM-LED		<p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m Distance, Smart Light, IP67, DC12V</p>		29.950.000
5	HAC-HFW1509TP-LED		<p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, HLC-Pro, BLC, 3D DNR, AGC, AWB 1 LED 20m Distance, Smart Light, IP67, DC12V</p>		29.500.000
6	HAC-HFW1509TP-A		<p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) <b>Built-in mic</b> 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, HLC-Pro, BLC, 3D DNR, AGC, AWB 1 LED 20m Distance, Smart Light, IP67, DC12V</p>		30.150.000
7	DH-HAC-HFW1500RP-Z-IRE6		<p>5MP Starlight HDCVI IR Bullet Camera, Image Sensor 1/2.7 inch CMOS Max 25 fps@5MP (16:9 video output) CVI/CVBS/AHD/TVI switchable 2.7 mm-12 mm motorized lens, 0.005 Lux/F1.6, 30IRE, 0 Lux IR on Illumination Distance 60 m , S/N Ratio &gt; 65 dB Pan/Tilt/Rotation Range Pan: 0°-360°, Tilt: 0°-90°, Rotation: 0°-360° Max. IR length 60 m, Smart IR, BLC/HLC/DWDR IP67, 12V DC</p>		40.150.000










توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
8	DH-HAC-HFW1500THP-I4 5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP (16:9 video output) 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max. IR length 40m, Smart IR, IP67, DC12V±30		19.900.000
9	DH-HAC-HFW1500THP-I8 5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP (16:9 video output) 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max. IR length 80m, Smart IR, IP67, DC12V±30		22.800.000
10	DH-HAC-HFW1500TP-0360B-S3 5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 30 m, Smart IR, IP67, DC12V		19.600.000
11	DH-HAC-HFW1500DP 5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6/Min. Illumination 0.005 Lux DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 80 m, Smart IR, IP67, DC12V		27.500.000
12	DH-HAC-HFW1500CMP 5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6/Min. Illumination 0.005 Lux DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 30 m, Smart IR, IP67, DC12V		19.600.000
13	HAC-B1A51 5MP HDCVI IR Bullet Camera, 1/2.7" 5 MegaPixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm, 2.8mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), BLC, HLC, AGC, AWB, 2D-DNR, Support OSD Menu, Max. IR length 20m, Smart IR, IP67, DC12V, Casing Plastic		15.000.000
14	DH-HAC-B2A51P 5MP HDCVI IR Bullet Camera, 1/2.7" 5 MegaPixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), BLC, HLC, AGC, AWB, 2D-DNR, Support OSD Menu, Max. IR length 20m, Smart IR IP67, DC12V, Casing Aluminium		17.500.000
15	DH-HAC-B1A41P 4MP HDCVI IR Bullet Camera, 1/2.7" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 3.6mm fixed lens HD and SD output switchable, Max. IR length 20m IP67, DC12V, Casing: Plastic		12.650.000
16	DH-HAC-B2A41P 4MP HDCVI IR Bullet Camera, 1/2.7" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 3.6mm fixed lens HD and SD output switchable, Max. IR length 20m IP67, DC12V, Casing: Aluminium		15.450.000
17	HFW1239TLMIP-IL-A 2MP Smart Dual Illuminators Bullet Camera Progressive CMOS - Focal Length 3.6 mm Max. 30 fps@1080p 0.001 lux@F1.6 (Color, 30 IRE) - 0.0001 lux(B/W, 30 IRE) - 0 lux (Illuminator on) Smart Dual Illuminators - Built-in-mic CVI/CVBS/AHD/TVI Switchable, Support OSD Menu 130 dB true WDR, HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m distance - 2 IR Lights 40m distance Smart IR & WL, IP67, DC12V		25.000.000
18	HFW1239MHP-A-LED 2MP Full-color HDCVI Bullet Camera, 1/2.8" CMOS ,24/7 color imaging Max. 30 fps@1080p, 3.6 mm fixed lens (6 mm optional) 50 m illumination distance , Super Adapt, 130 dB true WDR, 3D NR Focal Length 3.6 mm; 6 mm , Built-in mic ,CVI/CVBS/AHD/TVI switchable Min Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on , IP67, DC 12 V		28.400.000


توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
19	<p>DH-HAC-HFW1239TLMP-A-LED</p> <p>2M Full-color Starlight HDCVI Bullet Camera 1/2.8 inch 2.16 MP CMOS Minimum Illumination:0.005Lux/F1.6 1080@25fps, 720@25/50fps 3.6mm fixed lens <b>Built-in mic</b> CVI/CVBS/AHD/TVI Switchable WDR (130 db) , BLC, HLC, 2DNR,AGC,AWB Electronic Defog 40m LED distance, IP67, DC12V</p> 		22.700.000
20	<p>DH-HAC-HFW1239TLMP-LED</p> <p>2M Full-color Starlight HDCVI Bullet Camera 1/2.8 inch 2.16 Mega Pixels Progressive CMOS 0.005Lux/F1.6, 30IRE, 0Lux white Light on Max. 30fps@1080P 3.6mm fixed lens, 16x Digital Zoom CVI/TVI/AHD/CVBS Switchable, Support OSD Menu WDR (130 db)/E-Defog/BLC/HLC/AWB/AGC/2D DNR 40m LED Distance Smart Light, IP67, DC12V</p> 		22.350.000
21	<p>HAC-HFW1239TP-LED</p> <p>2MP Full-color HDCVI Bullet Camera 2MP 1/2.8" Progressive CMOS Max 2MP@25/30fps 3.6mm fixed lens CVI/CVBS/AHD/TVI switchable, Support OSD Menu WDR(130db), BLC, HLC, AWB, AGC, 3D DNR Smart Light, 1 LED 20m Distance, IP67, DC12V</p> 		21.450.000
22	<p>DH-HAC-HFW1231RP-Z-A</p> <p>2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination:0.002Lux/F1.5 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable,<b>Built in mic</b>, WDR(130dB), BLC, HLC, 3DNR, AGC,AWB 80m LED distance, Smart IR, IP67, DC12V</p>  		36.650.000
23	<p>DH-HAC-HFW1231RP-Z-IRE6</p> <p>2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination:0.002Lux/F1.5 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable WDR(130dB), BLC, HLC, 3DNR, AGC,AWB 80m LED distance, Smart IR, IP67, DC12V</p> 		35.750.000
24	<p>DH-HAC-HFW1230RP-Z-IRE6</p> <p>2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination:0.005Lux/F1.8 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable DWDR, BLC, HLC, 2DNR, AGC,AWB 60m LED distance, Smart IR, IP67, DC12V</p> 		32.450.000
25	<p>DH-HAC-HFW1230TP</p> <p>2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens (2.8mm, 6mm Optional) HD and SD output switchable, Support OSD Menu Starlight, DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V, Casing: Aluminium</p> 		15.650.000
26	<p>DH-HAC-HFW1230TP-A</p> <p>2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, <b>Built-in mic</b> DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V</p> 		16.100.000
27	<p>DH-HAC-HFW1230DP</p> <p>3.6mm Fixed lens, 25/30fps@1080P &amp; @720P DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, OSD Menu Max. IR length 80m, Smart IR, IP67, DC12V</p> 		20.700.000











توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار). دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
28 DH-HAC-HFW1220THP-I4	<p>2MP Value Starlight HDCVI IR Bullet Camera 1/2.7 inch CMOS 1080P@25fps, 720P@25fps, 720@50fps 3.6mm Fixed lens Value Starlight Minimum Illumination:0.008Lux/F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D DNR Smart IR, Eletronic Defog CVI/CVBS/AHD/TVI switchable Max. IR length 40m, Smart IR, IP67, DC12V</p>		16.100.000
29 HAC-HFW1209TLMP-LED-0360B	<p>2MP Full-color HDCVI Bullet Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 3.6mm Fixed lens Min. Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3D DNR CVI/CVBS/AHD/TVI switchable, OSD Menu Support 40m LED distance, IP67, DC12V</p>		17.850.000
30 HAC-HFW1209CMP-LED-0360B	<p>2MP Full Color Starlight HDCVI Bullet CCTV Camera 1/2.8 inch 2.16 Mega Pixels Progressive CMOS Max 30fps@2MP 3.6mm fixed lens CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V</p>		16.750.000
31 HAC-HFW1209CP-LED-0360B	<p>2MP Full-color HDCVI Bullet Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V</p>		13.550.000
32 HAC-HFW1200TLM-IL-A	<p><b>NEW</b></p> <p>2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera * In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version. 2 MP Progressive CMOS Sensor 3.6 mm Lens: H: 83°; V: 48°; D: 105° Max. 30 fps@1080p, CVI/CVBS/AHD/TVI switchable DWDR, BLC, HLC, AWB, AGC, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 40 m (131.23 ft) Warm light: 40 m (131.23 ft) , Super Adapt, 3D DNR, <b>Built-in mic, 1 Audio in</b> Min. Illumination 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on) 12 VDC, IP67, Metal+Plastic</p>		17.600.000
33 DH-HAC-HFW1200RP-Z-IRE6	<p>2MP HDCVI IR Bullet Camera, 1/2.7 inch CMOS Max 30fps@1080P, Min Illumination 0.02Lux/F1.7, 30IRE, 0Lux IR on Motorized vari-focal 2.7 mm-12 mm, Fixed iris BLC/HLC/DWDR , Gain Control , Noise Reduction 2D NR , Smart IR Max. IR length 60m,IP67, DC12V Built-in mic(-A)</p>		31.350.000
34 DH-HAC-HFW1200TLP	<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6 &amp; 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 40m, Smart IR, IP67, DC12V</p>		13.450.000
35 DH-HAC-HFW1200THP-A	<p>2MP HDCVI IR Bullet Camera 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens (2.8mm, 6mm Optional), <b>Built-in mic</b> HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 80m, Smart IR, IP67, DC12V</p>		15.400.000
36 DH-HAC-HFW1200THP-I4	<p>2MP HDCVI IR Bullet Camera 1/2.7 inch CMOS 1080P@25fps, 720P@25fps, 720@50fps 3.6mm Fixed lens Minimum Illumination:0.02Lux/F1.9 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Smart IR, Eletronic Defog HD and SD output switchable Max. IR length 40m, Smart IR, IP67, DC12V</p>		15.150.000











توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
37 DH-HAC-HFW1200DP-0360B-S5	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable, 3.6mm fixed lens Max. IR LEDs length 80m, Smart IR, IP67, DC12V		18.150.000
38 HAC-HFW1200CMP-0360B	2MP HDCVI IR Bullet Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP, 3.6mm fixed lens CVI/TVI/AHD/CVBS output switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 30m, Smart IR, IP67, DC12V		14.300.000
39 HAC-HFW1200CMP-A	2MP HDCVI IR Bullet Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP, 3.6mm fixed lens, <b>Built-in mic</b> CVI/TVI/AHD/CVBS output switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 30m, Smart IR, IP67, DC12V		15.400.000
40 HAC-HFW1200CM-IL-A	<b>NEW</b> 2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera <b>* In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version.</b> 2 MP Progressive CMOS Sensor 3.6 mm: H: 83°; V: 48°; D: 105° Max. 30 fps@1080p, CVI/CVBS/AHD/TVI switchable DWDR, BLC, HLC, AWB, AGC, 3D DNR, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 20m (65.62 ft) Warm light: 20m (65.62 ft), Super Adapt, Built-in mic, 1 Audio in Min. Illumination 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on) 12 VDC, IP67, Metal		16.850.000
41 DH-HAC-HFW1200SP	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V		14.400.000
42 DH-HAC-HFW1200TP	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 2.8mm/3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 25m, Smart IR, IP67, DC12V		15.000.000
43 DH-HAC-HFW1200TP-A	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens, <b>Built-in mic</b> HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V		15.400.000
44 DH-HAC-HUM3201B	1/2.8" 2Megapixel CMOS ( <b>Starlight</b> ), 25/30fps@1080P & @720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu WDR(120dB), Day/Night(ICR), AWB, AGC, BLC,HLC, 3DNR, DC12V		18.950.000
45 DH-HAC-B2A21P	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium		12.000.000
46 DH-HAC-B1A21P	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Plastic		9.750.000
47 DH-HAC-HDW1509TP-IL-A	5MP Smart Dual Illuminators Eyeball Camera Max 25 fps@5MP (16:9 video output). 120 dB true WDR, 3D NR Smart Dual Illuminators, 40 m illumination distance Super Adapt, Built-in MIC. 3.6 mm fixed lens (2.8 mm optional). CVI/CVBS/AHD/TVI switchable. IP67, 12 VDC.		37.300.000
48 DH-HDW1509TP-A-ALED	5MP Full-color HDCVI Eyeball Camera Progressive CMOS - Focal Length 2.8 mm Min. Illumination 0.001 Lux/F1.0, 0 Lux warm light on illumination 2 LEDs Distance 40 m <b>Built-in mic</b> , CVI/CVBS/AHD/TVI switchable WDR 120db, BLC, HLC, HLC-Pro, AWB, AGC, 3DNR Privacy Masking, Smart Light, IP67, DC 12V		31.800.000










**توجه:** دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
49	DH-HAC-HDW1509TLQP-A-LED 5MP Full-color HDCVI Quick-to-install Eyeball Camera 25fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu 120dB WDR, 3D/2D NR, Day/Night(ICR), AWB, AGC, BLC, HLC 20m illumination distance, Smart IR, IP67, DC12V, Built-in mic		30.250.000
50	DH-HAC-HDW1509TLQP-LED 5MP Full-color HDCVI Quick-to-install Eyeball Camera 25fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu 120dB WDR, 3D/2D NR, Day/Night(ICR), AWB, AGC, BLC, HLC 20m illumination distance, Smart IR, IP67, DC12V		27.200.000
51	DH-HAC-HDW1500SLP 5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR, IP67, DC12V		15.750.000
52	DH-HAC-HDW1500TRQP-A-0280B-S3 5MP Starlight HDCVI Quick-to-install IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 25/30 fps@5MP, 25/30fps@4MP,1080P@25/30 fps, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR,, Built-in Mic Max. IR LEDs length 20m, Smart IR, IP50, DC12V		18.950.000
53	DH-HAC-HDW1500TRQP-0280B-S3 5MP Starlight HDCVI Quick-to-install IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 25/30 fps@5MP, 25/30fps@4MP,1080P@25/30 fps, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR, IP67, DC12V		16.950.000
54	HAC-HDW1500CLQ-IL-A 5MP Smart Dual Light HDCVI Fixed-focal Quick-to-install Eyeball Camera * In order to use the 5MP 16:9 and the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version. 5MP Progressive CMOS Sensor 2.8 mm: H: 106°; V: 56°; D: 125° Max 25 fps@5MP (16:9 video output), CVI/CVBS/AHD/TVI switchable DWDR, BLC, HLC, AWB, AGC, 2D DNR, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 20m (65.62 ft) Warm light: 20m (65.62 ft), Super Adapt, Built-in mic Min. Illumination 0.05 lux@F1.6 (Color, 30 IRE) 0.005 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on) 12VDC, IP67, Plastic, Quick-to-install		23.000.000
55	HAC-T2A51P 5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP & @1080P (16:9 video output) 3.6mm & 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Aluminium		17.500.000
56	HAC-T1A51P 5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm and 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Plastic		14.650.000
57	DH-HAC-T2A41P 1/2.7" 4Megapixel CMOS, 25/30fps@4MP,25/30fps@1080P 2.8mm fixed lens, HD and SD output switchable Max. IR length 20m, IP67, DC12V, Casing: Aluminium		15.400.000
58	DH-HAC-T1A41P 1/2.7" 4Megapixel CMOS, 25/30fps@4MP,25/30fps@1080P 2.8mm fixed lens, HD and SD output switchable Max. IR length 20m, DC12V, Casing: Plastic		12.650.000

توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
59	<p>DH-HAC-HDW1239TLP-A-LED</p> <p>2M Full-color Starlight HDCVI Eyeball Camera 1/2.8 inch 2.16 Mega Pixels CMOS Minimum Illumination:0.005Lux/F1.6 Full-color starlight 1080@25fps, 720@25fps, 720@50fps 3.6 mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Smart Light, Electronic Defog HCVI/CVBS/AHD/TVI switchable <b>Built-in Mic</b> 20m LED distance, IP67, DC12V</p> <p>QUICK INSTALLATION</p> <p>STARLIGHT Full-color</p>		20.900.000
60	<p>DH-HAC-HDW1230MP</p> <p>2MP Starlight HDCVI IR Eyeball Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V</p> <p>STARLIGHT</p>		13.750.000
61	<p>HAC-HDW1209TLQP-A-LED-0280B</p> <p>2MP Full-color HDCVI Quick-to-install Eyeball Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 2.8mm fixed lens <b>Built-in Mic</b> CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V</p> <p>QUICK INSTALLATION</p> <p>Full-color</p>		16.000.000
62	<p>HAC-HDW1209TLQP-LED-0280B</p> <p>2MP Full-color HDCVI Quick-to-install Eyeball Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 2.8mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V</p> <p>QUICK INSTALLATION</p> <p>Full-color</p>		13.900.000
63	<p>DH-HAC-HDBW1200EP</p> <p>2MP HDCVI IR Dome Camera, 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 2.8mm Fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, IK10, DC12V</p>		15.100.000
64	<p>DH-HAC-HDW1200LP</p> <p>2MP HDCVI IR Eyeball Camera, 1/2.7" 2Megapixel CMOS Max 30fps@1080P, 2.1mm fixed lens HD and SD output switchable, <b>Built in Mic</b>, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 3m, Smart IR, IP67, DC12V</p> <p>Microphone icon</p>		17.950.000
65	<p>DH-HAC-HDW1200MP</p> <p>2MP HDCVI Quick-to-install IR Eyeball Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP 2.8mm/3.6mm fixed lens HD and SD output switchable, Support OSD Menu Day/Night(ICR), AWB, AGC, BLC, 2D-DNR Max. IR length 30m, Smart IR, IP67, DC12V</p>		12.900.000
66	<p>DH-HAC-HDW1200EMP-A Metal Case</p> <p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, <b>Built-in MIC</b> Day/Night(ICR), AWB, AGC, BLC, 2DNR, DWDR 3.6 &amp; 2.8mm fixed lens Max. IR LEDs length 50m, Smart IR, IP67, DC12V</p> <p>Microphone icon</p>		16.000.000
67	<p>HAC-HDW1200TRQP-A-0280B</p> <p>2MP HDCVI Quick-to-install IR Eyeball Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP 2.8mm/3.6mm fixed lens <b>Built in Mic</b> CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto switch by ICR Max. IR length 25m, Smart IR, IP50, DC12V</p> <p>QUICK INSTALLATION</p> <p>Microphone icon</p>		13.450.000
68	<p>DH-HAC-HDW1200TLP-A</p> <p>2MP HDCVI IR Eyeball Camera 1/2.7 inch CMOS Max 30fps@1080P 2.8mm Fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR <b>Built-in mic</b> Electronic Defog CVI/CVBS/AHD/TVI switchable Max. IR length 30m, Smart IR, IP67, DC12V</p> <p>Microphone icon</p>		14.200.000

توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
69	<p><b>HAC-HDW1200CLQ-IL-A</b></p> <p><b>DUAL LITE</b> <b>Full-color</b></p> <p><b>NEW</b></p> <p>2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera            * In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version.            2 MP Progressive CMOS Sensor 2.8 mm: H: 102°; V: 60°; D: 129°            Max. 30 fps@1080p, CVI/CVBS/AHD/TVI switchable            DWDR, BLC, HLC, AWB, AGC, 3D DNR, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 20m (65.62 ft) Warm light: 20m (65.62 ft), Super Adapt, Built-in mic, 1 Audio in            Min. Illumination 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)            12VDC, IP67, Plastic, Quick-to-install</p>		15.000.000
70	<p><b>DH-HAC-T2A21P</b></p> <p><b>Cooper Series</b></p> <p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P            2.8mm fixed lens            HD and SD output switchable, Support OSD Menu            DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR            Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium            1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P            2.8mm &amp; 3.6 fixed lens</p>		12.000.000
71	<p><b>DH-HAC-T1A21P</b></p> <p><b>Cooper Series</b></p> <p>HD and SD output switchable, Support OSD Menu            DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR            Max. IR length 20m, Smart IR, Casing: Plastic, DC12V            1/2.8" 2Megapixel Exmor R CMOS (Starlight)            Max 25/30fps @1080P &amp; 20/30/50/60fps @720P Resolution            4.8mm ~ 120mm 25x optical zoom            WDR (120db), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus            Max 400°/s pan speed, 360° endless pan rotation            Control over coaxial cable            1-channel BNC HDCVI/CVBS output (switchable)            Up to 300 presets, 5 auto scan, 8 tour, 5 pattern            Built-in 2/1 Alarm in/out, 1 Audio Input, RS485            IR Distance up to 150m, IP66, OSD</p>		9.500.000
72	<p><b>DH-SD59225I-HC-S2</b></p> <p><b>STARLIGHT</b></p> <p>2MP 30x Starlight IR PTZ HDCVI Camera, 1/2.8" Exmor R CMOS            Max. 25/30fps @1080P(1920x1080) &amp; 50/60fps @720P Resolution            4.5mm~135mm 30x optical zoom            WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus            Max 400°/s pan speed, 360° endless pan rotation            HD and SD switchable            Up to 300 presets, 5 auto scan, 8 tour, 5 pattern            Audio(in/out) 1 / 1 , Built-in 2/1 Alarm in/out            IR Distance up to 150m, IP66, OSD</p>		198.000.000
73	<p><b>SD59230I-HC</b></p> <p><b>STARLIGHT</b></p> <p>2MP 25x Starlight IR PTZ HDCVI Camera, 1/2.8" STARVIS CMOS            Max. 25/30fps @1080P(1920x1080) &amp; 50/60fps @720P Resolution            4.8mm~120mm 25x optical zoom            WDR(120dB), Day/Night(ICR), Ultra DNR, HLC, BLC, Auto iris, Auto focus            Max 400°/s pan speed, 360° endless pan rotation            Up to 300 presets, 5 auto scan, 8 tour, 5 pattern            HD and SD switchable, 2/1 Alarm In/Out            1CH Audio In, RS485, IR Distance up to 100m, IP66, OSD</p>		231.000.000
74	<p><b>DH-SD49225I-HC-LA</b></p> <p><b>STARLIGHT</b></p> <p>4CH Penta-brid 1080N/720P Real-Time Cooper Recorder            H.264 video compression, 4CH: 1/4 Playback            Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2 MP(20 Mbps)]            1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 8 TB            HDMI , VGA ,simultaneous video Output            2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support</p>		185.000.000
75	<p><b>DH-XVR1A04</b></p> <p><b>Cooper Series</b></p> <p>4 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR            H.265+/H.265/H.264+/H.264 dual-stream video compression            Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2MP(20 Mbps),            4CH: 1/4 Playback            HDMI , VGA ,simultaneous video Output            1 SATA port, up to 6 TB capacity            2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support            SMD Plus, Full channel AI-Coding, Human/Vehicle Classification</p>		21.750.000
76	<p><b>XVR1B04-I</b></p> <p><b>Cooper Series</b></p> <p>8CH Penta-brid 1080N/720P noneReal-Time Cooper Recorder            H.264 video compression, 8CH:1/4/9 Playback            Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 5 MP(40 Mbps)]            1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 8 TB            HDMI , VGA ,simultaneous video Output, 2*USB 2.0            10/100 Mbps LAN Interface, P2P Support</p>		26.300.000
77	<p><b>DH-XVR1A08</b></p> <p><b>Cooper Series</b></p>		26.750.000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.



مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
78 XVR1B08-I	<p><b>Wiz Sense AI</b></p> <p>8 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 6MP(40 Mbps), 4CH: 1/4/9 Playback HDMI , VGA ,simultanous video Output 1 SATA port, up to 6 TB capacity 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification</p> <p>Cooper Series</p>		32.000.000
79 XVR1B08H-I	<p><b>Wiz Sense AI</b></p> <p>8 Channels 5M-N/1080p Cooper 1U 1HDD Digital Video Recorder Supports Full-channel AI-Coding , H.265+/H.265 dual-stream Pentabrid (IP+CVI+AHD+TVI+CVBS) - Max 12 channels IP camera inputs Up to 8 channels SMD Plus Human/Vehicle Classification Encoding Capacity : 5M-N@(10 fps); 4M-N/1080p@(15 fps); 1080N@(25/30 fps) 1/4/8/9 Playback , 1 SATA port, up to 16 TB capacity 2*USB 2.0, Audio In/Out : 1/1 , 10/100 Mbps LAN Interface, P2P Support</p> <p>Cooper Series</p>		55.000.000
80 XVR5104HS-I3	<p><b>Wiz Sense AI</b></p> <p>New GUI V4.0 Support - 4 Channel Penta-brid 5M-N/1080p None Real-Time WizSense Ai XVR 5M-N; 4M-N; 1080p; 1080N; 720p; 960H; D1; CIF H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 6MP(32 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4ch 1 SATA Port up to 6 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support</p>		44.250.000
81 XVR5104HS-4KL-I3	<p><b>Wiz Sense AI 4K</b></p> <p>New GUI V4.0 Support - 4 Channel Penta-brid 4K WizSense Ai XVR 4K@7fps, 6MP@10fps, 5MP@12fps, 4MP@15fps, 4MN/1080p/720p@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 4+4 IP up to 8MP(64 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4ch 1 SATA Port up to 10 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support</p>		64.800.000
82 XVR5108HS-4KL(V.2)	<p><b>Wiz Sense AI</b></p> <p>New GUI V4.0 Support - 8CH Penta-brid 4K Recorder HDCVI 4K, AHD,5mp, HDTV 5MP 8+4ch support H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 8MP Tripwire, Intrusion, Face Detection, Smart Search 1/1 Audio In/Out, 1 SATA Port , Up to 8TB 1*HDMI, 1*VGA ,simultanous video Output 2*USB 2.0, 1*10/100 Mbps LAN Interface , P2P Support</p>		92.400.000
83 XVR5108HS-I3	<p><b>Wiz Sense AI</b></p> <p>New GUI V4.0 Support - 8 Channel Penta-brid 5M-N/1080p None Real-Time WizSense Ai XVR 5M-N; 4M-N; 1080p; 1080N; 720p; 960H; D1; CIF H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M 8+4 IP up to 6MP(64 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9ch 1 SATA Port up to 10 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 8ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification. IoT Suoport</p>		66.650.000

توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

<p>84 XVR5108HS-4KL-I2</p> <p><b>Wiz Sense</b> <b>AI</b></p>	<p><b>4K</b></p> <p>New GUI V4.0 Support - 8 Channel Penta-brid 4K-N/5MP WizSense Ai XVR                      4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps                      H.265+/H.265/H.264+/H.264 dual-stream video compression                      Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 8+8 IP up to 8MP(128 Mbps)                      HDMI/VGA Simultaneous Video Output, 1ch Audio I/O                      Playback 1/4/9ch                      1 SATA Port up to 10 TB capacity                      1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support                      2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Library, 8ch SMD Plus, Human/Vehicle Classification, IoT Support</p>	 <p>107.800.000</p>
<p>85 XVR5108HS-4KL-I3</p> <p><b>Wiz Sense</b> <b>AI</b></p>	<p>New GUI V4.0 Support - 8 Channels Penta-brid 4K-N/5MP                      Encode Capacity All channel 4K@(7 fps); 6MP@ (10 fps); 5MP@ (12 fps); 4K-N/4 MP/3 MP@ (15 fps); 4M-N/1080P @ (25/30fps);                      AI Coding/H.265+/H.265 dual-stream video compression                      Supports HDCVI/AHD/TVI/CVBS                      Up to 16 channels of IPC access / 128 Mbps                      Supports Full-channel AI Coding                      Perimeter Protection : 8 channels, 10 IVS for each channel / 2 channels (up to 12 face images/s) / Face Recognition : 2 channel up to 10 face databases / Full-channel SMD Plus                      Audio Input : 1, RCA (external) 8, BNC (coaxial) / Audio Output 1, RCA                      HDD Interface 1 SATA Port, up to 16TB                      RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000                      DC12V, 2A / Power Consumption Lower than 10 W / Operating Temperature -10 °C to +55 °C</p>	 <p>107.800.000</p>
<p>86 DH-XVR1B16</p> <p><b>Cooper Series</b></p>	<p>16CH Penta-brid 1080N/720P None Real-Time Cooper Recorder                      H.265+/H.265 dual-stream video compression                      1st channel 1080N/720P@25fps, others 1080N/720P@15fps                      16CH: 1/4/9/16 Playback                      Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 6 MP(64 Mbps)]                      1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 6 TB                      HDMI , VGA ,simultaneous video Output                      2 USB 2 , 10/100 Mbps LAN Interface, P2P Support</p>	 <p>52.800.000</p>
<p>87 XVR1B16-I</p> <p><b>Wiz Sense</b> <b>AI</b></p> <p><b>Cooper Series</b></p>	<p>8 Channel Penta-brid 1080N/720p Real-time WizSense Ai XVR                      H.265+/H.265/H.264+/H.264 dual-stream video compression                      Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 6MP(64 Mbps)                      4CH: 1/4/9/16 Playback                      HDMI/VGA Simultaneous Video Output                      1 SATA port, up to 6 TB capacity                      2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support                      8ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification</p>	 <p>64.750.000</p>
<p>88 XVR5116H-I2</p> <p><b>Wiz Sense</b> <b>AI</b></p>	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P WizSense Ai XVR                      5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps                      H.265+/H.265/H.264+/H.264 dual-stream video compression                      Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+4 IP up to 6MP(128 Mbps)                      HDMI/VGA Simultaneous Video Output, 1ch Audio I/O                      Playback 1/4/9/16ch                      1 SATA Port up to 10 TB capacity                      1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support                      2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>	 <p>111.100.000</p>
<p>89 XVR5116HS-S2(V.2)</p>	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P XVR                      5MN, 4M-N, 1080P, 1080N, 720P, 960H, D1, HD1, BCIF, CIF, QCIF                      H.264+/H.264 dual-stream video compression                      Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+8 IP up to 5MP(96 Mbps)                      HDMI/VGA Simultaneous Video Output, 1ch Audio I/O                      Playback 1/4/9/16ch                      1 SATA Port, up to 8TB capacity                      1 USB 2.0 , 1 USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support                      Tripwire, Intrusion, Face Detection</p>	 <p>95.400.000</p>

توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
90 XVR5116HS-I3	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P            Encode Capacity All channel 5M-N (10 fps); 4M-N/1080p (15fps)            AI Coding/H.265+/H.265 dual-stream video compression            Supports HDCVI/AHD/TVI/CVBS/IP video inputs            Max 24 channels IP camera, up to 6MP; Max 128Mbps incoming bandwidth            Supports Full-channel AI Coding / 16 channel SMD / 2 channel face recognition            Audio Input : 1, RCA (external) 16, BNC (coaxial) / Audio Output 1, RCA            HDD Interface 1 SATA Port, up to 16TB for a single HDD            RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000            DC12V, 2A / Power Consumption Lower than 12 W / Operating Temperature            -10 °C to +55 °C</p>		111.100.000
91 XVR5216AN-S2(V.2)	<p>New GUI V4.0 Support - 16CH Penta-brid 5MN/4M-N/1080P Non-real Time ,            1080N/720P Real-Time Recorder, 5MN/4M-N/1080P@15fps , 1080N/720P@25fps            H.264+/H.264 dual-stream video compression            1/4/9/16CH Playback, Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 MP(96            Mbps)]            Support Smart Search and Intelligent Video System            1/1 Audio In/Out, 2 SATA Port , Up to 16 TB            HDMI , VGA , simultaneous video Output, RS485 for PTZ support            2 USB Ports (1 USB 2.0 , 1 USB 3.0)            10/100/1000 Mbps LAN Interface, P2P Support</p>		123.800.000
92 XVR5216AN-I2	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P WizSense Ai XVR            5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps            H.265+/H.265/H.264+/H.264 dual-stream video compression            Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+4 IP up to 6MP(128 Mbps)            HDMI/VGA Simultaneous Video Output, 1ch Audio I/O            Playback 1/4/9/16ch            2 SATA Port up to 10 TB capacity each port(20TB Total)            1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support            2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to            10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		142.500.000
93 XVR5216AN-I3	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P            Encode Capacity All channel 5M-N (10 fps); 4M-N/1080p (15fps)            AI Coding/H.265+/H.265 dual-stream video compression            Supports HDCVI/AHD/TVI/CVBS            16+8 channels, each IP Channel up to 6MP            Supports Full-channel AI Coding            Perimeter Protection : 2 channel, 10 IVS for each channel / Face Detection : 6            attributes , 2 channels each channel up to 12 faces / Face Recognition : 2 channel up to            10 face databases / Full-channel SMD Plus            Audio Input : 1, RCA (external) 16, BNC (coaxial) / Audio Output 1, RCA            HDD Interface 2 SATA Port, up to 16TB for a single HDD            RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000            DC12V, 2A / Power Consumption Lower than 12 W / Operating Temperature            -10 °C to +55 °C</p>		142.500.000
94 XVR5216AN-4KL-I2	<p>New GUI V4.0 Support - 16 Channel Penta-brid 4KN/5MP WizSense Ai XVR            4K@7fps, 6MP@10fps, 5MN@12fps, 4KN/4MP@15fps, 4MN/2MP/1MP@25/30fps            H.265+/H.265/H.264+/H.264 dual-stream video compression            Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+16 IP up to 8MP(128 Mbps)            HDMI/VGA Simultaneous Video Output, 1ch Audio I/O            Playback 1/4/9/16ch            2 SATA Port up to 10 TB capacity each port(20TB Total)            1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support            2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to            20,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		215.800.000

توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
95 DH-XVR5216AN-4KL	<p>New GUI V4.0 Support - 16 Channel Embedded Processor 16+8 Channel, each channel up to 8M HDCV 4K, 4MP, 1080P@25/30fps, 720P@50/60fps, 720P@25/ Record rate Main stream: 4K(1~7fps);4MP(1~15fps);1080P (1~25/30f) H.264+/H.26 dual-stream video compression Internal HDD 2 SATA Ports, up to 8TB capacity for each IP Camera Input 8+4/16+8 Channel, each channel up to 8 Audio In/Out 1/1, RC - 2 USB Ports (1 USB 2.0 , 1 USB 3), 1*RS485, 1*1000 Mbps</p>		186.000.000
96 DH-XVR5216AN-4KL-13	<p>New GUI V4.0 Support - 16 Channels Penta-brid 4K-N/5MP Encode Capacity All channel 4K@(7fps); 6MP@(10fps); 5MP@(12fps); 4K-N/4MP/3MP@(15fps); 4M-N/1080P(25/30fps); AI Coding; H.265+; H.265; H.264+; H.264 Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 32 channels IP camera inputs, each channel up to 8MP Supports Full-channel AI Coding Perimeter Protection : Advanced Model: 2 channels , General Model: 8 channels ; Face Detection : 2 channels ;Face Recognition : 2 channels , Up to 10 face databases , SMD Plus : 16 channels Audio Input :1-channel RCA , 16-channel BNC 16 / Audio Output 1, RCA HDD Interface 2 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 12 VDC, 5A / Power Consumption Lower than 15 W(without HDD) / Operating Temperature-10 °C to +55 °C</p>		215.800.000
97 DH-XVR5232AN-S2(V.2)	<p>New GUI V4.0 Support - 32CH Penta-brid 1080P Recorder 4M-N/1080P@15fps, 1080N/720P@25fps H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 MP(128 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 2 SATA Port , Up to 16 TB 1*HDMI, 1*VGA ,simultaneous video Output RS485 for PTZ support, 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface, P2P Support</p>		199.100.000
98 XVR5232AN-I2	<p>New GUI V4.0 Support - 32 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 32ch IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		230.500.000
99 XVR5232AN-I3	<p>New GUI V4.0 Support - 32 Channels Penta-brid 5M-N/1080P Encode Capacity All channels 5M-N@(10fps); 4M-N/1080P@(15fps) AI Coding/H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS 32 IP channels,up to 6MP / bandwidth: 128 Mbps Supports 16-channel AI Coding Perimeter Protection : Up to 4 channels 10 IVS for each channel / Face Detection :2 channels (up to 12 face images/s) / Face Recognition : Up to 2 channels, Up to 10 face databases /16 channels SMD Plus) Audio Input : 1, RCA (external) 32, BNC (coaxial) / Audio Output 1, RCA HDD Interface 2 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 DC12V, 5A / Power Consumption Lower than 17 W / Operating Temperature -10 °C to +55 °C</p>		230.500.000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
100 XVR5432L-13	<p>32 Channels Penta-brid 5M-N/1080P 4HDDs WizSense Digital Video Recorder            H.265+/H.265 dual-stream video compression.            Supports 16-channel AI-Coding.            Supports HDCVI/AHD/TVI/CVBS/IP video inputs.            Max 32 channels IP camera, each channel up to 8MP; 128 Mbps bandwidth.            Up to 8 channels video stream (analog channel) perimeter protection.            Up to 16 channels video stream (analog channel) SMD plus.            Up to 2 channels video stream (analog channel) human face recognition.            Perimeter Protection, Face Detection, Face Recognition : Up to 10 face databases with 10,000 face images, SMD Plus            Multi-screen Display 1/4/8/9/16/25/36            IoT &amp; POS functionalities.</p>		379.500.000
101 DH-XVR4232AN-I	<p>32 Channels Penta-brid 1080N/720P 1U 2HDDs WizSense Digital Video Recorder            Video Compression AI Coding; H.265+; H.265; H.264+; H.264            Supports 8-channel AI-Coding.            Supports HDCVI/AHD/TVI/CVBS/IP video inputs.            Max 16 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth. Multi-screen Display 1/4/8/9/16/25/36            Audio Input 1-channel RCA (external) 32-channel BNC (coaxial audio)            Two-way Talk, HDD Interface 2 SATA ports, up to 16 TB            Up to 16 channels video stream (analog channel) SMD Plus.            Long transmission distance over coax cable.</p>		154.000.000



MIP CCTV

فروشگاه: خیابان جمهوری، نبش شیخ هادی، مجتمع تجاری یگانه، طبقه همکف، پلاک ۲  
 دفتر مرکزی: میدان توحید، نصرت غربی، خیابان کاظم بیگی، بن بست دوم پلاک ۴، واحد ۳