




Accessories			
Items	Description	User Price	
PoE Switches (Unmanaged)			
1	<p>DS-3E0105P-E</p> <p>IEEE 802.3at/af Power over Ethernet (PoE) compliant 4 x 10/100Mbps Auto-MDIX PoEports 1, 100Mbps Ethernet Uplink Port Provides up to 30 watts per PoE port PoE power budget 58W 4 KV surge protection for PoE ports 1 Gbps switching fabric 448 Kbits RAM Data Buffer Sturdy metal enclosure</p>	IRR 7,350,000	
2	<p>DS-3E0109P-E</p> <p>IEEE 802.3at/af Power over Ethernet (PoE) compliant 8 x 10/100Mbps Auto-MDIX PoEports 1, 100Mbps Ethernet Uplink Port Provides up to 30 watts per PoE port PoE power budget 123W 4 KV surge protection for PoE ports 1.8 Gbps switching fabric 1.25 MbitsRAM Data Buffer Sturdy metal enclosure</p>	IRR 19,150,000	
3	<p>DS-3E0318P-E</p> <p>IEEE 802.3at/af Power over Ethernet (PoE) compliant 16x10/100Mbps Auto-MDIX PoEports 2, 1000Mbps Combo Uplink Port Provides up to 30 watts per PoE port PoE power budget 230W 4 KV surge protection for PoE ports 7.2 Gbps switching fabric 2.75 MbitsRAM Data Buffer Sturdy metal enclosure</p>	IRR 42,840,000	
4	<p>DS-3E0326P-E</p> <p>IEEE 802.3at/af Power over Ethernet (PoE) compliant 24x10/100Mbps Auto-MDIX PoEports 2, 1000Mbps Combo Uplink Port Provides up to 30 watts per PoE port PoE power budget 370W 4 KV surge protection for PoE ports 8.8 Gbps switching fabric 2.75 MbitsRAM Data Buffer Sturdy metal enclosure</p>	IRR 64,780,000	
PoE Switches (Web Management)			
5	<p>DS-3E1310P-E</p> <p>802.3af/at PoE standard 8-core power supply technology, reducing the power circuit loss Data monitor and control for the important ports transmission distance: 250 meters Buffer optimization to guarantee the video data transmission VLAN configurable,Port trunk,STP, multicast ,port mirroring QoS,SNMP,WEB management,Store-and-forward switching IEEE802.3, IEEE802.3u and IEEE802.3x network standards MTBF (Mean Time Between Failure) ≥ 100,000 hours All-metal enclosed construction Table-mounted and rack-mouted design for convenient installation</p>	IRR 23,760,000	



6	DS-3E1318P-E	802.3af/at PoE standard 16 * 100M PoE Port 2 * 1000M COMBO Port 8-core power supply technology, reducing the power circuit loss,Data monitor and control for the important ports, transmission distance : 250 meters Buffer optimization to guarantee the video data transmission VLAN configurable,Port trunk,STP, multicast ,port mirroring QoS,SNMP,WEB management, Store-and-forward switching IEEE802.3, IEEE802.3u and IEEE802.3x network standards MTBF (Mean Time Between Failure) ≥ 100,000 hours All-metal enclosed construction Table-mounted and rack-mouted design for convenient installation	IRR 58,340,000	
		Network Cables		
8	DS-1LN6-UE-W	UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.530mm CM Rating -کابل شبکه Cat6 UTP باقابلیت ارسال دیتا تا سرعت 1 گیگابایت درثانیه به همراه پهنای باند 250 مگاهرتز قابل عرضه درحلقه های 305متری به همراه تست FLUKE	IRR 18,200,000	
		Brackets		
9	DS-1LN6-UU	UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.565mm CM Rating -کابل شبکه Cat6 UTP باقابلیت ارسال دیتا تا سرعت 1 گیگابایت درثانیه به همراه پهنای باند 250 مگاهرتز قابل عرضه درحلقه های 305متری به همراه تست FLUKE	IRR 20,030,000	
		Vertical pole mount, Hik white , Aluminum alloy , 117×194×310mm , Suitable for: DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx		
10	DS-1602ZJ-pole	Vertical pole mount, Hik white , Aluminum alloy , 117×194×310mm , Suitable for: DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx	IRR 5,870,000	
		Pendant mount , Hik white , Aluminum alloy , Φ116.5×500mm Suitable for: DS-2DE/AE4xxx DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx		
11	DS-1662ZJ	Pendant mount , Hik white , Aluminum alloy , Φ116.5×500mm Suitable for: DS-2DE/AE4xxx DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx	IRR 4,660,000	
		Ceiling mount , Hik white , Aluminum alloy , Φ116.5×57mm Suitable for: DS-2DE/AE4xxx DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx		
12	DS-1663ZJ	Ceiling mount , Hik white , Aluminum alloy , Φ116.5×57mm Suitable for: DS-2DE/AE4xxx DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx	IRR 1,810,000	



13	DS-1661ZJ	Pendent Mounting Bracket In/Outdoor, Color: Hik white Material: Aluminum alloy Dimension: 116.5×200mm Weight: 600g	IRR 3,090,000	
14	DS-1693ZJ	Wall mount , Hik white , steel , 190×200×500mm , 5700g Suitable for PTZ positioner	IRR 3,000,000	
15	DS-1681ZJ	Ceiling mount , Hik white , Aluminum alloy Suitable for: DS-2DE/AE4xxx DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx	IRR 1,360,000	
16	DS-1602ZJ	Wall mount , Hik white , Aluminum alloy , 97×182×305mm Suitable for: DS-2DE/AE4xxx DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx	IRR 3,730,000	
17	DS-1273ZJ-135B	Wall mount , White , Aluminum alloy , with junction box , Φ135×182×120mm Suitable for: DS-2CD27xx	***	
Keyboard				
18	DS-1100KI	Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup	IRR 100,760,000	
19	DS-1005KI	network Keyboard, USB interface, support Hikvision VMS, NVR, DVR	IRR 45,100,000	
Tester				
21	DS-TT-X41T	7" LCD Screen, Support HDTVl camera, Up the Coax, 12 VDC output	IRR 29,000,000	