






لیست قیمت محصولات تحت شبکه هایک ویژن HIKVISION NETWORK PRODUCTS PRICE LIST

No	Model	Specs	Pic	price
1	DS-2CD2T86G2-4I(4mm)	<p>4K AcuSense Fixed Bullet Network Camera Excellent low-light performance with powered-by-DarkFighter technology 1/1.8" Progressive Scan CMOS 0.003 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR 4mm, Fixed Lens WDR 120 dB,SNR 52 dB, BLC,HLC,3D DNR Supplement Light Range up to 80 m IR Wavelength 850 nm support micro SD card, up to 256 GB Smart Event : Scene change detection Deep Learning Function : Face Capture, Line crossing detection, intrusion detection, region entrance detection, region exiting detection, Supports human and vehicle targets classification Material : Metal Reset Key / IP67 / PoE</p>		115.000.000
2	DS-2CD2T87G2-LK	<p>4K ColorVu Fixed Bullet Network Camera 1/1.2" Progressive Scan CMOS 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with Light 4mm, Fixed Lens WDR 130 dB,SNR 52 dB, BLC,HLC,3D DNR Supplement Light Range up to 60 m IR Wavelength 850 nm support micro SD card, up to 256 GB Smart Event: Scene change detection Deep Learning Function: Face Capture, Line crossing detection, intrusion detection, region entrance detection, region exiting detection Material: Front cover: metal, back cover: metal Reset Key / IP67 / PoE</p>		123.500.000
3	DS-2CD2666G2-IZS	<p>6 MP AcuSense Powered-by-DarkFighter Motorized Varifocal Bullet Network Camera 1/2.4" Progressive Scan CMOS Color: 0.003 Lux @ (F1.4, AGC ON), B/W: 0 Lux with IR Varifocal lens, motorized lens, 2.8 to 12 mm WDR 120 dB,SNR 52 dB, BLC,HLC,3D DNR Supplement Light Range up to 60 m IR Wavelength 850 nm support micro SD card, up to 256 GB Audio: 1 input, 1 output Alarm: 1 input, 1 output Smart Event: Scene change detection Deep Learning Function: Face Capture, Line crossing detection, intrusion detection, region entrance detection, region exiting detection Supports human and vehicle targets classification. Material: Metal Reset Key / IK10 / IP67 / PoE</p>		173.000.000



<p>4</p> <p>DS-2CD2T66G2-4I(4mm)</p>	<p>6 MP AcuSense Fixed Bullet Network Camera Excellent low-light performance with powered-by-DarkFighter technology 1/2.4" Progressive Scan CMOS 0.003 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR 4mm, Fixed Lens WDR 120 dB, SNR 52 dB, BLC, HLC, 3D DNR Supplement Light Range up to 80 m IR Wavelength : 850 nm support micro SD card, up to 256 GB Smart Event : Scene change detection Deep Learning Function : Face Capture, Line crossing detection, intrusion detection, region entrance detection, region exiting detection (support alarm triggered by specified target types (human and vehicle)), Scene change detection Material : Metal Reset Key / IP67 / PoE</p>	 <p>call</p>
<p>5</p> <p>DS-2CD2T63G2-4I(4mm)</p>	<p>6 MP AcuSense Fixed Bullet Network Camera 1/2.8" Progressive Scan CMOS 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR 4mm, Fixed Lens WDR 120 dB, SNR 52 dB, BLC, HLC, 3D DNR Supplement Light Range up to 80 m IR Wavelength : 850 nm support micro SD card, up to 256 GB Smart Event : Face detection Material : Aluminum alloy body Reset Key / IP67</p>	 <p>79.300.000</p>
<p>6</p> <p>DS-2CD2163G2-IU</p>	<p>6 MP AcuSense Vandal Fixed Dome Network Camera 1/2.4" Progressive Scan CMOS Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR 2.8mm, Fixed Lens WDR 120 dB, SNR 52 dB, BLC, HLC, 3D DNR Supplement Light Range up to 30 m IR Wavelength : 850 nm support micro SD card, up to 512 GB Built in Mic - Noise Filter Smart Event: Line crossing detection, intrusion detection (support alarm triggering by specified target types (human and vehicle)) - Face detection Material: Aluminum alloy body - Bubble: plastic IP67 / IK10 / POE / Reset Key</p>	 <p>72.800.000</p>
<p>7</p> <p>DS-2CD2063G2-I</p>	<p>6 MP AcuSense Fixed Bullet Network Camera 1/2.4" Progressive Scan CMOS Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR 4mm, Fixed Lens WDR 120 dB, SNR 52 dB, BLC, HLC, 3D DNR Supplement Light Range Up to 40 m IR Wavelength : 850 nm support micro SD card, up to 512 GB Smart Event: Line crossing detection, intrusion detection (support alarm triggering by specified target types (human and vehicle)) - Face detection Material: Aluminum alloy body - IR cover: plastic Reset Key / IP67 / POE</p>	 <p>71.000.000</p>
<p>8</p> <p>DS-2CD1653G0-IZ</p>	<p>5 MP Varifocal Bullet Network Camera 1/2.7" Progressive Scan CMOS 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR Varifocal lens, motorized lens, 2.8 to 12 mm WDR 120 dB, BLC, 3D DNR Supplement Light Range Up to 50 m IR Wavelength : 850 nm support microSD card, up to 256 GB Reset Key / IP67 / PoE</p>	 <p>94.800.000</p>



9	DS-2CD1053G0-I	<p>5 MP Fixed Bullet Network Camera 1/2.7" Progressive Scan CMOS 0.01 Lux @ (F2.0, AGC ON), B/W: 0 Lux with IR 4mm, Fixed Lens WDR 120 dB, BLC, 3D DNR Supplement Light Range Up to 30 m IR Wavelength 850 nm IP67 / PoE</p>		43.000.000
10	DS-2CD1153G0-I	<p>5 MP Fixed Dome Network Camera 1/2.7" Progressive Scan CMOS 0.01 Lux @ (F2.0, AGC ON), B/W: 0 Lux with IR 4mm, Fixed Lens WDR 120 dB, BLC, 3D DNR Supplement Light Range Up to 30 m IR Wavelength 850 nm IP67 / PoE</p>		44.100.000
11	 DS-2CD1T57G0-L	<p>5 MP ColorVu Fixed Bullet Network Camera 1/2.7" Progressive Scan CMOS Color: 0.001 Lux @ (F1.0, AGC ON), 0 Lux with light 4 mm, Fixed Lens WDR 120 dB, BLC, 3D DNR White Light Range Up to 50 m Material - Front cover: metal, body: plastic, bracket: metal IP67 / PoE</p>		71.500.000
12	 DS-2CD2643G2-IZS	<p>4 MP AcuSense Motorized Varifocal Bullet Network Camera 1/3" Progressive Scan CMOS Color: 0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR on Varifocal lens, motorized lens, 2.8 to 12 mm WDR 120 dB, SNR 52 dB, BLC, HLC, 3D DNR Supplement Light Range : U+p to 60 m IR Wavelength: 850 nm Audio: 1 Input, 1 Output Alarm: 1 input, 1 Output Built-in microSD, up to 512 GB Smart Event: Line crossing detection, intrusion detection (support alarm triggering by specified target types (human and vehicle)) - Face detection Material: Aluminum alloy body IP67 / PoE / Reset Key</p>		128.000.000
13	 DS-2CD2646G2-IZS	<p>4 MP AcuSense Motorized Varifocal Bullet Network Camera 1/3" Progressive Scan CMOS H.265+, DarkFighter technology Color: 0.003 Lux @ (F1.4, AGC ON), B/W: 0 Lux with IR Varifocal lens, motor-driven lens, 2.8 to 12 mm WDR 120db, SNR 52db, BLC, HLC, 3D DNR Supplement Light Range Up to 60 m Audio I/O 1/1, Alarm I/O 1/1 microSD card, up to 512 GB Smart Event Line crossing detection, intrusion detection, region entrance detection, region exiting detection (support alarm triggering by specified target types (human and vehicle)), Scene change detection, Face Capture Water and dust resistant (IP67) and vandal resistant (IK10)</p>		138.000.000
14	 DS-2CD2143G2-I	<p>4 MP AcuSense Fixed Dome Network Camera 1/3" Progressive Scan CMOS Color: 0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR on 2.8 mm, Fixed Lens WDR 120 dB, SNR 52 dB, BLC, HLC, 3D DNR Supplement Light Range Up to 30 m IR Wavelength : 850 nm support micro SD card, up to 512 GB Smart Event: Line crossing detection, intrusion detection (support alarm triggering by specified target types (human and vehicle)) - Face detection Material: Aluminum alloy body - Bubble: plastic IP67 / PoE / Reset Key</p>		63.800.000

15	 DS-2CD1047G0-L	4 MP ColorVu Fixed Bullet Network Camera 1/3" Progressive Scan CMOS 0.001 Lux @ (F1.0, AGC ON), B/W: 0 Lux with white light 4 mm, Fixed Lens WDR 120 dB, BLC, 3D DNR White Light Range Up to 30 m Material : Aluminum alloy body IP67 / PoE		50.500.000
16	 DS-2CD1347G0-L	4 MP ColorVu Fixed Turret Network Camera 1/3" Progressive Scan CMOS 0.001 Lux @ (F1.0, AGC ON), B/W: 0 Lux with white light 2.8 mm, Fixed Lens WDR 120 dB, BLC, 3D DNR White Light Range Up to 30 m Material : Metal & Plastic IP67 / PoE		51.600.000
17	 DS-2CD2047G2-L	4 MP ColorVu Fixed Mini Bullet Network Camera 1/1.8" Progressive Scan CMOS 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light 4 mm, Fixed Lens WDR 130 dB, SNR 52 dB, BLC, HLC, 3D DNR Supplement Light Range 40 m Smart Event : Scene change detection Deep Learning Function : Face Capture, Line crossing detection, intrusion detection, region entrance detection, region exiting detection support micro SD card, up to 256 GB Reset Key / IP67 / PoE		78.500.000
18	 DS-2CD2147G2-L	4 MP ColorVu Fixed Dome Network Camera 1/1.8" Progressive Scan CMOS 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light 4 mm, Fixed Lens WDR 130 dB, SNR 52 dB, BLC, HLC, 3D DNR Supplement White Light Range Up to 30 m Smart Event : Line crossing detection, intrusion detection, region entrance detection, region exiting detection, Scene change detection Deep Learning Function : Face Capture support micro SD card, up to 256 GB Reset Key / IP67 / PoE		call
19	 DS-2CD2347G2-L(U)	4 MP ColorVu Fixed Turret Network Camera 1/1.8" Progressive Scan CMOS Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light 4 mm, Fixed Lens WDR 130 dB, SNR 52 dB, BLC, HLC, 3D DNR Supplement White Light Range Up to 30 m BUILT in Mic - Noise Filter Smart Event: Line crossing detection, intrusion detection, region entrance detection, region exiting detection - Scene change detection support micro SD card, up to 512 GB Material: Aluminum alloy body, except for trim ring Reset Key / IP67 / PoE		86.200.000
20	 DS-2CD1043G0-I	4MP Fixed Bullet Network Camera 1/3" progressive scan CMOS 0.01 Lux @ (F2.0, AGC ON), B/W: 0 Lux with IR 4 mm, Fixed Lens WDR 120 dB, BLC, 3D DNR Supplement Light Range Up to 30 m IR Wavelength : 850 nm Material : Metal & Plastic IP67 / PoE		38.600.000



فیدار پردازش خاورمیانہ

۰۲۱۶۲۹۹۹۰۲۱

آدرس فروشگاه مرکزی: خیابان جمهوری، نبش خیابان شیخ هادی، مجتمع تجاری یگانه، طبقه همکف پلاک ۲
آدرس دفتر مرکزی: میدان توحید، خیابان پرچم، خیابان کاظم بیگی، بن بست دوم، پلاک ۴، طبقه سوم واحد ۳

21	DS-2CD1143G0-I	<p>4MP Fixed Dome Network Camera 1/3" progressive scan CMOS 0.01 Lux @(F2.0, AGC ON), B/W: 0 Lux with IR 2.8 mm, Fixed Lens WDR 120 dB, BLC, 3D DNR Supplement Light Range Up to 30 m IR Wavelength : 850 nm Material : Aluminum alloy body IP67 / PoE</p>		40.600.000
22	DS-2CD1143G0-IUF	<p>4MP Fixed Dome Network Camera 1/3" progressive scan CMOS 0.01 Lux @(F2.0, AGC ON), B/W: 0 Lux with IR 2.8 mm, Fixed Lens WDR 120 dB, BLC, 3D DNR Supplement Light Range Up to 30 m IR Wavelength : 850 nm Bult in Mic - Noise Filter Material : Aluminum alloy body IP67 / PoE</p>		43.300.000
23	DS-2CD1023G0E-I	<p>2 MP Fixed Bullet Network Camera 1/2.7" Progressive Scan CMOS 0.01 Lux @(F2.0, AGC ON), B/W: 0 Lux with IR 4mm, Fixed Lens Digital WDR, BLC, 3D DNR - SNR 52 dB Supplement Light Range Up to 30 m IR Wavelength : 850 nm Material : Metal & Plastic IP67 / PoE</p>		28.000.000
24	DS-2CD1123G0E-I	<p>2 MP Fixed Dome Network Camera 1/2.7" Progressive Scan CMOS 0.01 Lux @(F2.0, AGC ON), B/W: 0 Lux with IR 2.8 mm, Fixed Lens Digital WDR, BLC, 3D DNR Supplement Light Range Up to 30 m IR Wavelength : 850 nm Material : Metal & Plastic IP67 / PoE</p>		30.500.000
25	DS-2CD1027G0-L	<p>2 MP ColorVu Fixed Bullet Network Camera 1/2.8" Progressive Scan CMOS 0.001 Lux @ (F1.0, AGC ON) 4mm, Fixed Lens Digital WDR, BLC, HLC, 3D DNR Supplement Light Range Up to 30 m Material : Metal IP67 / PoE</p>		33.300.000
26	DS-2CD1327G0-L	<p>2 MP ColorVu Fixed Turret Network Camera 1/2.8" Progressive Scan CMOS 0.001 Lux @ (F1.0, AGC ON), 0 Lux with white light 2.8 mm, Fixed Lens Digital WDR, BLC, 3D DNR White Light Range Up to 30 m Camera Material : Metal & Plastic IP67 / PoE</p>		33.300.000
27	DS-2CD1323G0E-I	<p>2 MP Fixed Turret Network Camera 1/2.7" Progressive Scan CMOS Color: 0.01 Lux @(F2.0, AGC ON), B/W: 0 Lux with IR 2.8 mm Fixed Lens Digital WDR, BLC, 3D DNR Supplement Light Range Up to 30 m Camera body: metal, bottom base : plastic IP67 / PoE</p>		29.500.000



فیدار پردازش خاورمیانہ

۰۲۱۶۲۹۹۹۰۲۱

آدرس فروشگاه مرکزی: خیابان جمهوری، نبش خیابان شیخ هادی، مجتمع تجاری یکانه، طبقه همکف پلاک ۲
آدرس دفتر مرکزی: میدان توحید، خیابان پرچم، خیابان کاظم بیگی، بن بست دوم، پلاک ۴، طبقه سوم واحد ۳

<p>28</p> <p>DS-2DE4425IW-DE(T5)</p>	<p>4-inch 4 MP 25X Powered by DarkFighter IR Network Speed Dome 1/2.8" progressive scan CMOS 0.005 Lux @ (F1.6, AGC ON); B/W: 0.001 Lux @ (F1.6, AGC ON), 0 Lux with IR 4.8 mm to 120 mm PTZ Lens Horizontal field of view: 55° to 2.4° - Vertical field of view: 33° to 1.4° H.265+, Ultra Low Light 25x Optical Zoom - 16x digital Zoom Presets : 300 - Patrol Scan : 8 patrols - 4 pattern IR Distance: up to 100 m WDR 120 dB - SNR 52 dB - Digital defog - EIS Smart Event : Line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection, audio exception detection Deep Learning Function : Face Capture, Line crossing, intrusion, region entrance, region exiting Support alarm triggering by specified target types (human and vehicle) Alarm 1 input, 1 output - Audio 1 input, 1 output - Reset - microSD card up to 256 GB Material : ADC12 IP66 / PoE</p>	 <p>262.000.000</p>
<p>29</p> <p>DS-2DE5225IW-AE</p>	<p>5-inch 2 MP 25X Powered by DarkFighter IR Network Speed Dome 1/2.8" Progressive Scan CMOS 0.005 Lux @(F1.6, AGC ON) 4.8 mm to 120 mm PTZ Lens field of view: 57.6° to 2 - Vertical field of view: 34.4° to 1 H.265+, Ultra Low Light 25x Optical Zoom - 16x digital Zoom Presets : 300 - Patrol Scan : 8 patrols - 4 pattern IR Distance: up to 150 m - 1-ch audio input - 1-ch audio output WDR 120 dB - HLC/BLC/3D DNR/Defog/EIS/Regional Exposure/Regional Foc Smart Event : Face detection, line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection, audio exception detection Alarm 2 inputs, 1 output - Audio 1 input, 1 output - Reset, microSD card up to 256 GB Material : Metal IP66 / PoE</p>	 <p>call</p>
<p>30</p> <p>DS-7104NI-Q1 /M</p>	<p>4-CH 1U - Up to 4 MP resolution Incoming Bandwidth 40 Mbps Outgoing Bandwidth 60 Mbps HDMI/VGA Output 1920*1080P/60Hz Decoding format H.265+/H.265/ H.264+/H.264 Decode Capability 1-ch @ 4 MP / 2-ch @ 1080p SATA 1 SATA interface -Up to 6TB Power supply 12 VDC Working temperature -10 to +55° C (+14 to +131° F)</p>	 <p>31.500.000</p>
<p>31</p> <p>DS-7608NI-K1</p>	<p>8-ch 1U 4K NVR Incoming Bandwidth 80 Mbps Outgoing Bandwidth 80 Mbps HDMI Output 4K/30Hz, VGA Output 1080/60Hz Smart Function : 4-ch Motion Detection 2.0, Support multiple VCA (Video Content Analytics) events, Support multiple VCA (Video Content Analytics) events Audio Output 1-ch, Two Way Audio, Alarm I/O N/A H.265+/H.265/H.264+/H.264, up to 8MP, Playback 8-ch Decoding Capability 1-ch@8 MP (30 fps)/5-ch@1080p (30 fps) 1, RJ-45 10 /100 Mbps 1 SATA HDDs up tp 8 TB 12 VDC, 1.5 A, Working Temperature -10 to +55° C (14 to 131° F) Working Humidity 10 to 90 %</p>	 <p>64.000.000</p>





فیدار پردازش خاورمیانه

۰۲۱۶۲۹۹۹۰۲۱

آدرس فروشگاه مرکزی: خیابان جمهوری، نبش خیابان شیخ هادی، مجتمع تجاری یگانه، طبقه همکف پلاک ۲
آدرس دفتر مرکزی: میدان توحید، خیابان پرچم، خیابان کاظم بیگی، بن بست دوم، پلاک ۴، طبقه سوم واحد ۳

<p>32</p> <p>DS-7616NI-K2</p>	<p>16-ch 1U 4K NVR Incoming Bandwidth 160 Mbps Outgoing Bandwidth 160 Mbps HDMI Output 4K/30 Hz, VGA Output 1080/60 Hz HDMI/VGA independent output Smart Function : Support multiple VCA (Video Content Analytics) events, Configurable special camera smart functions, such as VCA detection (motion, line crossing, intrusion, etc.) and ANPR Audio I/O 1/1, Two Way Talk, Alarm I/O 4/1 H.265/H.265+/H.264/H.264+, up to 12MP, Playback 16-ch, Decoding Capability 1-ch@12 MP (30 fps)/2-ch@8 MP (30 fps)/4-ch@4 MP (30 fps)/8-ch@1080p (30 fps) 1, RJ-45 10/100/1000 Mbps 2 SATA HDDs up to 10TB for each Port 12 VDC, 3.33A, Working Temperature -10 °C to 55 °C (14 °F to 131 °F), Working Humidity 10 to 90 %</p>	 <p>89.000.000</p>
<p>33</p> <p>DS-7732NXI-I4/S</p>	<p>32-ch 1U AcuSense 4K NVR Incoming Bandwidth 256 Mbps Outgoing Bandwidth 256 Mbps Decoding Capability 16-ch @ 1080p (30 fps) Recording Resolution: 32 MP/24 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA /4CIF/DCIF/2CIF/CIF/QCIF HDMI 1 Output: 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz HDMI 2 Output: 1920 × 1080/60Hz VGA Output: 1-ch, 1920 × 1080/60Hz Video Output Mode: HDMI1/VGA simultaneous output, HDMI2/VGA independent output AI by Device: Facial recognition, perimeter protection, motion detection 2.0 AI by Camera: Facial recognition, perimeter protection, video structuralization, throwing objects from building, motion detection 2.0, ANPR, people counting, VCA Engine: 1, engine mode is adjustable Facial Recognition with Attributes - Up to 16 face libraries, with up to 10,000 face pictures in total Motion Detection 2.0: By Device 16-ch- By Camera All channels Perimeter Protection: By Device- Up to 4-ch 2 MP (H.264/H.265) -By Camera All channels ANPR: By Camera All channels Network Interface: 2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface SATA: 4 SATA interfaces supporting hot-plug Up to 10TB eSATA: 1 eSATA interface</p>	 <p>350.000.000</p>
<p>34</p> <p>DS-7732NI-K4</p>	<p>32-ch 1.5U 4K NVR Incoming Bandwidth 256 Mbps Outgoing Bandwidth 160 Mbps HDMI Output 4K/30Hz, VGA Output 1080/60 Hz HDMI/VGA independent output Smart Function : Support multiple VCA (Video Content Analytics) events, Configurable special camera smart functions, such as VCA detection (motion, line crossing, intrusion, etc.), heat map, ANPR, and people counting Audio Output 1-ch, Two Way Talk, Alarm I/O 16/4 H.265/H.265+/H.264+/H.264/MPEG4, up to 12MP, Playback 16-ch, Decoding Capability 1-ch@12MP (30fps)/2-ch@8 MP (30 fps)/4-ch@4 MP (30 fps)/8-ch@1080p(30 fps) 2, RJ-45 10/100/1000 Mbps 4 SATA HDDs up to 10TB for each port 100 to 240 VAC, 50 to 60Hz, Working Temperature -10 °C to 55 °C (14 °F to 131 °F), Working Humidity 10 to 90 %</p>	 <p>203.000.000</p>



35	DS-9632NI-I8	<p>32-ch 2U 4K NVR Incoming Bandwidth 320 Mbps Outgoing Bandwidth 256 Mbps HDMI 1 Output 4K/60Hz, HDMI 2 Output 1080/60Hz VGA 1 Output 1080/60Hz, VGA 2 Output 1080/60Hz HDMI 1 and VGA 1 provide simultaneous video output, and work as the main output HDMI 2 and VGA 2 provide simultaneous video output, and work as the auxiliary output Smart & POS Function : Supports multiple VCA (Video Content Analytics) event Smart search for the selected area in the video; and smart playback to improve the playback efficiency, Supports VCA search for fire/ship/temperature/temperature difference detection triggered vid, POS information overlay on live view and playback, POS triggered recording and alarm Audio Output 2-ch, Two-Way Audio 1-ch, Alarm In/Out 16/4 H.265+/H.265/H.264+/H.264/MPEG4 Decoding Capability 1-ch@32 MP (30 fps)/2-ch@12 MP (20fps)/4-ch@8 MP (25fps)/8-ch@4 MP (30fps)/16-ch@1080p (30fps) 2, RJ-45 10/100/1000 Mbps 8 SATA interfaces supporting hot-plug Up to 10TB capacity for each disk RAID Type : RAID0, RAID1, RAID5, RAID6, and RAID10 (at least 4 TB for each HDD) eSATA : 1 eSATA interface Working Temperature -10 °C to 55 °C (14 °F to 131 °F), Working Humidity 10% to 90%</p>		680.000.000
36	DS-9664NI-I8	<p>64-ch 2U 4K NVR Incoming Bandwidth 320 Mbps Outgoing Bandwidth 256 Mbps Incoming Bandwidth(RAID Mode): 200 Mbps Outgoing Bandwidth(RAID mode): 200 Mbps HDMI 1 Output: 4K (3840 × 2160)/60Hz - HDMI 2 Output: 1920 × 1080/60Hz - VGA 1 Output: 1920 × 1080/60Hz - VGA 2 Output: 1920 × 1080/60Hz Video Output Mode: HDMI 1 and VGA 1 provide simultaneous video output, and work as the main output; HDMI 2 and VGA 2 provide simultaneous video output, and work as the auxiliary output Decoding Capability: 1-ch@32 MP (30 fps)/2-ch@12 MP (20fps)/4-ch@8 MP (25fps)/8-ch@4 MP (30fps)/16-ch@1080p (30fps) RAID Type RAID0, RAID1, RAID5, RAID6, and RAID10 (at least 4 TB for each HDD) SATA8 SATA interfaces supporting hot-plug - Up to 10TB for each HDD Alarm In/Out 16/4</p>		890.000.000



فیدار پردازش خاورمیانه

۰۲۱۶۲۹۹۹۰۲۱

آدرس فروشگاه مرکزی: خیابان جمهوری، نبش خیابان شیخ هادی، مجتمع تجاری یگانه، طبقه همکف پلاک ۲
 آدرس دفتر مرکزی: میدان توحید، خیابان پرچم، خیابان کاظم بیگی، بن بست دوم، پلاک ۴، طبقه سوم واحد ۳