
























Hilook-Camera-DVR

Items	Description	User Price	
1	THC-B110-M 1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), IP66	IRR 6,500,000	
2	THC-B120-P 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66	IRR 9,250,000	
3	THC-B120-MS 2 MP Audio Fixed Mini Bullet Camera Smart IR, up to 20 m IR distance Water and dust resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together	IRR 10,500,000	
4	THC-B120-M 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66-METAL	IRR 9,500,000	
5	THC-B120-MPIRL 2 MP PIR Fixed Mini Bullet Camera 2 MP, 1920 × 1080 resolution, 2.8 mm, 3.6 mm fixed focal lens, Smart IR, up to 20 m IR distance, PIR detection, strobe light alarm IP66	IRR 9,500,000	
6	THC-B140-P 4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- -DWDR-BLC-IP66	IRR 11,500,000	
7	THC-B140-M 4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- -DWDR-IP 66-BLC-Full Metal	IRR 13,500,000	
8	THC-B220 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS-IP66	IRR 10,500,000	

9	THC-B220C	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance- Switchable TVI/AHD/CVI/CVBS-IP66	IRR 11,500,000	
10	THC-B220-M	2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8/3.6/6mm Lens, Support HD TVI/AHD/CVI/CVBS video output-Full Metal	IRR 11,750,000	
11	THC-B240	4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-BLC-IP 66	IRR 13,500,000	
12	THC-B240-M	4MP CMOS Sensor, EXIR Bullet, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR-DWDR, OSD Menu, IP66, 2.8/3.6/6mm Lens,Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 16,500,000	
13	THC-T110-P	1 MP high-performance CMOS, 1280 × 720 resolution, 2.8 mm, 3.6 mm, 6 mm fixed focal lens, Day/Night switch, EXIR 2.0, smart IR, up to 20 m IR distance, 4 in 1 video output (switchable TVI/AHD/CVI/CVBS), Switchable TVI/AHD/CVI/CVBS. Pelastic case	IRR 4,750,000	
14	THC-T120-C	2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 8,500,000	
15	THC-T120	2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 8,500,000	
16	THC-T123	2 MP EXIR Turret Camera-performance CMOS- Ultra low light- 1920 × 1080 resolution- 2.8 mm, 3.6 mm, 6 mm fixed lens- Day/Night switch EXIR 2.0, smart IR, up to 30 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)	IRR 6,000,000	
17	THC-T120-MS	2 MP Audio Fixed Turret Camera Smart IR, up to 20 m IR distance Water resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together	IRR 9,750,000	

18	THC-T120-M	2 MP high-performance CMOS- 1920 × 1080 resolution- 2.8 mm , fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 8,500,000		
19	THC-T140-P	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm , Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) DWDR-BLC-IP66			
20	THC-T140	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm , Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) DWDR-BLC-IP66	IRR 9,750,000		
21	THC-T140-M	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm , Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) DWDR-BLC-IP66-METAL	IRR 11,500,000		
22	THC-T220-P	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm ,fixed focal lens-Day/ Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 8,750,000		
23	THC-T220-PC	2 MP Fixed Turret Camera Smart IR, up to 40 m IR distance Water resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 8,750,000		
24	THC-T220-MC	HiLook 2MP EXIR Turret Cam with Fixed Lens 1080p turret camera Smart IR, up to 40 m IR distanceWater resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)			
25	THC-T220-MS	2 MP Audio Fixed Turret Camera Smart IR, up to 40 m IR distanceWater resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together			

26	THC-T220-M	2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm ,fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 9,500,000	
27	THC-T240-P	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66	IRR11,000,000	
28	THC-T240-M	4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66-METAL	IRR 14,500,000	
Vari-Focal Series				
29	THC-B320-VF	2MP CMOS Sensor, 40m IR , Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR,, DWDR- DNR, OSD Menu, IP66, 2.8-12mm Vari Focal Lens , Support HD-TV/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 19,500,000	
30	THC-B340-VF	4MP CMOS Sensor - 2.8-12mm Vari Focal Lens , EXIR Bullet, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR, OSD Menu, IP66 , Support HD-TV/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 23,500,000	
31	THC-D320-VF	2MP CMOS Sensor, 40m IR , EXIR Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens --support HD-TV/AHD/CVI/CVBS video output-,IK10-Full Metal	IRR 12,500,000	
32	THC-D340-VF	4MP CMOS Sensor, EXIR Dome, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens ,IK10, Support HD-TV/AHD/CVI/CVBS video output-Full Metal	IRR 16,500,000	
33	THC-T320 VF	2MP CMOS Sensor, 40m IR , EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu, IP66, 2.8-12mm Vari Focal Lens , Support HD-TV/AHD/CVI/CVBS video output-Cover&Base:Plastic- Eyeball: Metal	IRR 14,500,000	

34	THC-T340-VF	4MP CMOS Sensor, EXIR Eyeball, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu , IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic-Eyeball: Metal	IRR 16,500,000	
Turbo HD PTZ Camera				
35	PTZ-T4225I-D	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 25× optical zoom, 16× digital zoom 120 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning SwitchableTVI/AHD/CVI/CVBS video outputs	■	
36	PTZ-T4215I-D	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 15× optical zoom, 16× digital zoom 120 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	■	
37	PTZ-T5225I-A	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 25× optical zoom DWDR (Digital Wide Dynamic Range) Up to 150 m IR distance 3D intelligent positioning Switchable turbo HD and CVBS outputs	■	
DVR 4 Channel				
38	DVR-104G-F1	4-ch 1080p Mini 1U Lite H.264 DVR,5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback.	IRR 18,500,000	
39	DVR-204G-F1	Recording Capability HD1080p Lite 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 1-ch Up to 960P resolution), 1 SATA (6TB)interface, HD1080p Lite @ 25 fps/ch, 260 1U case-- HDMI output HD1080p-Metal	IRR 21,500,000	
40	DVR-204Q-F1	Recording Capability 3MP 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, 1-ch IP video input(up to HD1080p resolution), 1 SATA (6TB) interface, CH 1: 3MP @ 12 fps, CH 2-4:1920×1080P: 12 fps/ch, 260 1U case-- HDMI outputHD1080p-Metal	IRR 29,500,000	

MPCCTV

فیدار پردازش خاورمیانه

نماینده رسمی برترین برند های حفاظت الکترونیک

خط ویژه: ۰۲۱-۶۲۹۹۹۰۲۱

لیست قیمت هایلوک

DORSA HiLook
TADBIR ANDISHAN

41	DVR-204Q-K1	H265+ compression saving up to 50% on bandwidth and storage. Recording 2MP@15FPS on 1080P or @25FPS on 1080PLite (3MP@15FPS on channel 1) Support self-adaptive HDTV/HDCVI/AHD/CVBS signal input.Add up to 2 x 6MP IP cameras.HDMI output at 1920 x 1080 resolution Up to 4-ch synchronous playback at 1080p resolution playback at up to 256X speed.	IRR 31,500,000	
42	DVR-204U-F1	Recording Capability 5MP/3MP 4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 2-ch IP video input(up to 6MP resolution) , 1 SATA (6 TB) - interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case- HDMI output HD1080p-Metal	IRR 37,500,000	
43	DVR-204U-K1	Self-adaptive HDTV/HDCVI/AHD/CVBS signal input I Up to 8/16-ch 8 MP IP cameras input for DVR-204/208U-K1 I 8 MP/5 MP/4 MP HDTV video input and live view for DVR-208U-K1, and 5MP/4 MP for DVR-204U-K1 I Defogging function enabled for the supported analog cameras I Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal	IRR 38,500,000	
DVR 8 Channel				
44	DVR-108G-F1	8-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback.	IRR 23,500,000	
45	DVR-208G-F1	Recording Capability HD1080p Lite 8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 2-ch Up to 960P resolution) , 1 SATA(6TB) interface, HD1080p Lite @ 12 fps/ch, 260 1U case-- HDMI output HD1080p-Metal	IRR 29,500,000	
46	DVR-208Q-F1	Recording Capability 3MP 8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, - 2-ch IP video input(up to HD1080p resolution) , 1 SATA(6TB) interface, CH 1 & 2: 3MP @ 12 fps, CH 3 - 8:1920x1080P: 12 fps/ch, 260 1U case- HDMI output HD1080p-Metal	IRR 42,500,000	

MPCCTV

فیدار پردازش خاورمیانه




نماینده رسمی برترین برند های حفاظت الکترونیک

خط ویژه: ۰۲۱-۶۲۹۹۹۰۲۱

لیست قیمت هایلوک

DORSA HiLock
TADBIR ANDISHAN

47	DVR-208Q-K1	Connectable to turbo HD, AHD, HDCVI and analog cameras. 2-ch 1080p IP cameras input. Long distance transmission over UTP and coaxial cable One key enable H.264+ compression. Up to 3 MP resolution for recording of the first 2 channels. Supports real-time 1080p lite. Simultaneous HDMI/VGA output at up to 1920 x 1080 resolution. One SATA interface (up to 6TB capacity per HDD).	IRR 47,500,000	
48	DVR-208Q-K2	8-ch 1080p 1U H.265 DVR-5 signals input adaptively (HDTV/ AHD/ CVI/ CVBS/ IP)-Long distance transmission over UTP and coaxial cable-H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs-Supports 4 MP lite, and when enabled the image effect is similar with 4 MP- Encoding ability up to 1080p lite @ 15 fps-Two HDDs for continuous video recording Smart search for efficient playback.	IRR 52,500,000	
49	DVR-208U-F1	Recording Capability 5MP/3MP 8-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input- 4-ch IP video input(up to 6MP resolution), 1 SATA (6 TB) interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@2 5fps (P)/30fps (N), 315 1U case- HDMI output 4K-Metal	IRR 62,500,000	
50	DVR-208U-K1	8 Channel DVR,Support HD-TVI, AHD, HD-CVI and analog cameras Supports 4 x IP Camera,1080P resolution real-time recording 8MP recording @ 8fps,VGA output at up to 1920 x 1080P resolution HDMI output at up to 4K (3840 x 2160) resolution,Supports h.265+ Support up to 8-ch synchronous playback,Internet & Smart Phone compatible	IRR 64,500,000	
Digital Video Recorder				
51	DVR-116G-F1	16-ch 1080p Mini 1U Lite H.264 DVR, 5 signals input adaptively (HDTV/ AHD/ CVI/ CVBS/ IP),Long distance transmission over UTP and coaxial cable,H.265 Pro+ compression to improve encoding efficiency and reduce data storage costsSupports 1080p lite,Encoding ability up to 1080p lite @ 12 fps,One HDD for continuous video recording,Smart search for efficient playback.	IRR 37,500,000	
52	DVR-216G-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 42,500,000	

53	DVR-216G-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920×1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 37,500,000	
54	DVR-216Q-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920×1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 62,500,000	
55	DVR-216Q-F2	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 2 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920×1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 65,500,000	
56	DVR-216Q-K1	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 67,500,000	
57	DVR-216Q-K2	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 69,500,000	
58	DVR-216U-F2	Recording Capability 5MP/3MP 16-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 8-ch IP video input(up to 6MP resolution), 2 SATA (6 TB)-interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@2 5fps (P)/30fps (N), 380 1U case-HDMI output 1ch 4K-Metal-	IRR105,000,000	

MIP CCTV

فیدار پردازش خاورمیانه

نماینده رسمی برترین برند های حفاظت الکترونیک




خط ویژه: ۰۲۱-۶۲۹۹۹۰۲۱

لیست قیمت هایلوک



DORSA
TADBIR ANDISHAN

HiLook

59	DVR-216U-K2	DVR 16 Channels HD 8 Megapixel, Interfaces input: 16 video / 1 Audio, (Support (TVI - AHD – CVI - CVBS, HDMI, VGA Outputs, 2 USB Support H.265+ compression, 2SATA up to 8TB capacity per HDD, Up to 8-ch, 6MP IP cameras input, Up to 8 MP resolution for recording	IRR 115,000,000	
60	DVR-232G-K2	32-ch 1080p Lite 1U H.265 DVR, transmission over UTP and coaxial cable H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs Supports 1080p lite, and when enabled the image effect is similar with 1080p Encoding ability up to 1080p lite @ 12 fps, 2HDDs for continuous video recording	IRR 72,920,000	
61	DVR-232Q-K2	32-ch 1080p 1U H.265 DVR 5 signals input adaptively (HDTV/ AHD/ CVI/ CVBS/ IP) H.265 Pro+ compression to improve encoding efficiency and reduce data storage costs, Supports 4 MP lite, and when enabled the image effect is similar with 4 MP, Encoding ability up to 1080p lite @ 15 fps 2 HDDs for continuous video recording	IRR 135,000,000	

www.mipcctv.com